

# FLEXIBLE PROFILES: PRAPFLEX

## CHARACTERISTICS

Flexible extruded PMMA highly resistant profile with a white diffusing cover. Can be used to follow curved lines; minimum curve diameter 43 cm

## CAN BE USED WITH LED STRIPS WITH MAXIMUM WIDTH:

12 mm.

## MAXIMUM POWER:

10W/m

## INSTALLATION

Surface installation. Attach using the clips provided.



## ACCESSORIES INCLUDED

Installation kit included 5 mt.: 10 steel clips, 5 side caps without hole and 5 side caps with holes for cabling.

Installation kit included 20 mt.: 40 steel clips, 20 side caps without hole and 20 side caps with holes for cabling.

## PACKAGE

Available in two different lengths: L=5m or L=20m Spare accessories available with separate code



PARALLEL EMISSION TO THE PLANE



Cutting Project profiles to size\*:

fixed cost of piece work

VA04

\* Includes mounting accessories.

IP20


art.	Description	L1	H	L	8011905	
<b>PRAPFLEX5</b> ◆	flexible PMMA profile and accessories	18	11,50	5000	844714	1
<b>PRAPFLEX20</b> ◆	flexible PMMA profile and accessories	18	11,50	20000	844721	1



◆ To be discontinued



art	Description	8011905	
<b>PRAPFLEX-EC</b> ◆	5+5 PC end caps	933494	1



art	Description	8011905	
<b>PRAPFLEX-CL</b> ◆	5 sets of metal clips	933463	1

◆ To be discontinued