


1E3279EL | JEDI COMPACT Outdoor Projector

Adjustable linear LED projector



	4000K	H(m)	D1(m)	D2(m)	E _{max} (lx)		
	Ra80	28°	78°				
	Fixture Power	28W	1	0.55	1.70	2417	
	Source Flux	3600lm	2	1.11	3.40	604	
	Fixture Flux	2706lm	3	1.66	5.10	269	
	Efficacy	97lm/W	4	2.22	6.79	151	
TS1092	I _{max} =774cd/klm	I _{max}	2785cd	5	2.77	8.49	97



SOURCE

High Power High Efficiency Ra80 linear LED board. Ra90 on request.

- Energy efficiency class:** D
- Nominal power:** 24W
- Nominal flux:** 3600lm
- Colour rendering index:** 80
- Rf:** 82.6
- Rg:** 95.7
- CCT nominal:** 4000K
- SDCM:** 3
- Lifetime (L80/B10):** >50000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

Internal optical system composed of a primary cylindrical glass lens, a high reflectance anodised aluminium reflector and an integrated holographic filter. Wall Washer version.

- Optic:** WALL WASHER
- Beam angles:** WW
- Optical efficiency:** 75%
- Fixture flux:** 2706lm
- Luminous efficacy:** 97lm/W
- Photobiological safety:** Compliant with RG1 low risk group

MECHANICAL CHARACTERISTICS

Extruded anodised aluminium 15µ body. Extra clear 5mm thick glass flat screen. The body of the fixture is adjustable and can be installed away from the mounting surface using accessory snap brackets.

- Colour and finish:** Aluminium
- Dimensions:** L=576mm
- Weight:** 2.6Kg
- Version:** INTEGRATED DRIVER
- Degree of protection:** IP66,IP67
- Mechanical Resistance:** IK08

ELECTRICAL CHARACTERISTICS

Integrated driver version. Complete with electronic ON-OFF power supply. Pre-cabled with a 1 metre 3x1mm² H07RN-F cable. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

- Fixture Power:** 28W
- Power supply:** 220-240Vac 50/60Hz
- Insulation Class:** CLASS 1
- Type of driver / Control:** ON-OFF
- Driver included:** YES
- Class F:** YES
- SAFE FLICKER:** PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light
- Ambient temperature:** -25°C / +35°C

INSTALLATION

To be completed with stainless steel adjustable brackets.

NOTES

Uses the "Waterblock Smart" technical solution that involves resin coating the connection cables, limiting the risk of humidity reaching the driver or the fixture. 110-277Vac version available on request.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656



1E3279EL | JEDI COMPACT Outdoor Projector

Adjustable linear LED projector

Related codes

Bracket

Code
1E3304

Stainless steel short bracket kit for surface installation (2 pieces).
Rotation +/-90°.

Code
1E3306

Stainless steel long bracket kit for surface installation (2 pieces).
Rotation +/-90°.

Accessories

Grid



L mm	H mm	P mm	Colour	Code
560	48	57	●	1E3905

Asymmetric grid in stainless steel, powder-painted.
External mounting respect to fixture.

Ray Shade



L mm	H mm	P mm	Colour	Code
570	48	59	●	1E3909

Hood in stainless steel, powder-painted.
External mounting respect to fixture.



L mm	H mm	Colour	Code
576	54	●	1E3913

Adjustable hood in stainless steel, powder-painted.
External mounting respect to fixture.

Tool



Code
1E3305

Tightening wrench for the connector kit.

Connector



Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm².
Cable diameter range from 7 to 12mm.



Code
1E2494

Multiple connection box IP68.
1 IN - 3 OUT 4 poles max. wire section 2.5mm².
Cable diameter range from 6 to 12mm.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A.: FI-275656

TARGETTI

1E3279EL | JEDI COMPACT Outdoor Projector
Adjustable linear LED projector**Surge protector**

Code

A013A

Surge protector compatible with CLASS I lighting fixtures.

Operating voltage 230-277Vac.

SPD type 2+3.

Max surge protection 10kV.

CLASS I

IP67

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI