




1E3533DA90 | MR SMITH

Wall-mounted LED fixture



	2700K	H(m)	D1(m)	D2(m)	E _{max} (lx)		
	Ra90		96°	81°			
	Fixture Power	13W	1	2.25	1.72	219	
	Source Flux	1606lm	2	4.49	3.45	55	
	Fixture Flux	998lm	3	6.74	5.17	24	
	Efficacy	75lm/W	4	8.99	6.90	14	
TS1435	I _{max} =155cd/klm	I _{max}	249cd	5	11.23	8.62	9



The figures on the drawing are expressed in mm.

SOURCE

High efficiency Chip on Board LED Ra90. 3500K on request.

Energy efficiency class: E

Nominal power: 12W

Nominal flux: 1606lm

Colour rendering index: 90

Rf: 92

Rg: 99

CCT nominal: 2700K

Lifetime (L80/B10): >50000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

MicroPet, high reflectance white spotlight. Version with direct/indirect emission.

Emission: DIRECT/INDIRECT

Optic: OPAL

Optical efficiency: 62%

Fixture flux: 998lm

Luminous efficacy: 75lm/W

Photobiological safety: Compliant with RG1 low risk group

MECHANICAL CHARACTERISTICS

Painted die-cast anodised aluminium body. Injection moulded opal polycarbonate screen.

Colour and finish: Ferrite

Dimensions: AxB=130x130mm

Weight: 0.75Kg

Degree of protection: IP65

Mechanical Resistance: IK08

ELECTRICAL CHARACTERISTICS

230V version with built-in DALI driver.

Fixture Power: 13W

Power supply: 220-240Vac 50/60Hz

Insulation Class: CLASS 1

Type of driver / Control: DALI - PUSH

Driver included: YES

Class F: YES

SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

Ambient temperature: -25°C / +35°C

INSTALLATION

Wall-mounted version with direct attachment on the rear frame of the product.

NOTES

Casambi control system available using a dedicated accessory. Uses the "Waterblock Smart" technical solution that involves resin coating the connection cables, limiting the risk of humidity reaching the driver or the fixture. It is possible to subject the product to Cataphoresis treatment on request. 110-277Vac version available on request. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

1E3533DA90 | MR SMITH
Wall-mounted LED fixture

Accessories

Control systems




Code
1E3048
IP67 wireless control unit with DALI interface. It generates a local DALI2 bus, enabling a direct connection to a DALI interface LED driver. The module can only be used in a closed system and cannot be connected to an existing DALI network. The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 5.0 technology. The devices automatically create an adaptive, robust, and reliable wireless mesh network, allowing for the easy and efficient management of a high number of fixtures. The control unit is preset to the DALI 1CH profile, meaning the device can control a single DALI driver with broadcast commands. In addition to the DALI broadcast, other operating modes are available, such as: • Button (normally open) • Control unit 0/1-10V • Control unit DALI Tunable White DT8 • Presence sensor



Code
1E4369
IP67 Extender for wireless control of LED driver with dimming DALI interface based on Casambi technology. It has a DALI2 output with the capacity to control up to 40 lighting fixtures. With the addition of a further external BUS DALI power supply it is possible to control up to 64 fixtures. IP67 Extender is preset to the DALI broadcast profile, meaning all the luminaires connected to it are dimmable at the same level. In addition to the DALI broadcast other operating modes are available, such as: • EXTENDER DALI 8CH • EXTENDER DALI Tunable White • EXTENDER DALI 4CH • EXTENDER DALI DT8 Tunable White

Surge protector



Code
A013A
Surge protector compatible with CLASS I lighting fixtures. Operating voltage 230-277Vac. SPD type 2+3. Max surge protection 10kV. CLASS I IP67



Code
A013C
Surge protector compatible with CLASS I lighting fixtures. DALI, DMX, 0-10V datalines compliance. Operating voltage 230Vac. SPD type 2+3. Max surge protection 10kV. CLASS I IP20