


## 1E4131CA | IVY Multiple projector

Adjustable LED 3x light module, powered at low voltage, to be installed into the installation profile



|        |                |        |       |          |
|--------|----------------|--------|-------|----------|
|        | 3500K          | H(m)   | D(m)  | Emax(lx) |
|        | Ra90           |        | 53°   |          |
|        | Fixture Power  | 7W     | 1     | 717      |
|        | Source Flux    | 823lm  | 2     | 179      |
|        | Fixture Flux   | 581lm  | 3     | 80       |
|        | Efficacy       | 88lm/W | 4     | 45       |
| TS1647 | Imax=871cd/klm | Imax   | 717cd | 5        |
|        |                |        | 5.01  | 29       |



### SOURCE

High efficiency Chip on Board LED Ra90.

**Energy efficiency class:** F

**Nominal power:** 3x5,9W

**Nominal flux:** 3x823lm

**Colour rendering index:** 90

**Rf:** 91

**Rg:** 100

**CCT nominal:** 3500K

**SDCM:** 3

**Lifetime (L80/B10):** >50000h tq +25°C

### ILLUMINOTECHNICAL CHARACTERISTICS

WFL beam. Optic equipped with an acrylic collimator lens and integrated holographic diffusive filter.

**Optic:** LENS

**Beam angles:** WFL

**Optical efficiency:** 71%

**Fixture flux:** 3x581lm

**Luminous efficacy:** 88lm/W

**Photobiological safety:** Compliant with RG1 low risk group

### MECHANICAL CHARACTERISTICS

Cylindrical aluminium bodies obtained through CNC machining process and protected with a layer of black anodization with a minimum thickness of 15µ. Powder painted Ferrite grey. Tempered extra clear front glasses. Aluminium joints with locking system. Adjustability of the optical units of 90° on the vertical plane (friction locking system) and 355° on the horizontal plane with the possibility of mechanical aiming locking through no tools system. Electronic components hosted inside a polymeric plastic box sealed by a silicone rubber gasket.

**Colour and finish:** Ferrite

**Dimensions:** L=442mm

**Weight:** 1.1Kg

**Version:** CASAMBI

**Degree of protection:** IP65

### ELECTRICAL CHARACTERISTICS

**Fixture Power:** 3x7W

**Power supply:** 48Vdc

**Insulation Class:** CLASS 3

**Class F:** YES

**Ambient temperature:** -25°C / +35°C

### INSTALLATION

Fast connection system of the modules through anodized aluminium clips. Free positioning all over the installation profile according to installation needs with mechanical lock through Hex Key. Designed for connection in series through H05RN-F (0.15m + 0.15m) cable completed with male/female miniaturised IP65 connectors.

### NOTES

Version with built-in Casambi control system (Casambi Ready). DALI control system available using a special accessory. The photometrics refer to individual projectors. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

### WARRANTY

5 years.

### WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.  
Via Pratese, 164  
50145 Firenze - Italy  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

CCIAA Firenze  
Share Capital:  
€ 500.000,00  
VAT N. (IT):  
01537660480  
R.E.A.: FI-275656

**TARGETTI**

# 1E4131CA | IVY Multiple projector

Adjustable LED 3x light module, powered at low voltage, to be installed into the installation profile

## Related codes

### Power Supply



| Driver | Colour | Code          |
|--------|--------|---------------|
| ON-OFF | ●      | <b>1E4169</b> |

48Vdc driver box (IP65).  
L=450mm 90W.  
Equipped with connection cable H05RN-F (0.15m + 0.15m) complete with male/female IP65 connectors for 220V and miniaturized female IP65 connector for 48V.



| Driver | Colour | Code          |
|--------|--------|---------------|
| ON-OFF | ●      | <b>1E4175</b> |

48Vdc driver box (IP65).  
L=450mm 150W.  
Equipped with connection cable H05RN-F (0.15m + 0.15m) complete with male/female IP65 connectors for 220V and miniaturized female IP65 connector for 48V.

### Power Supply

| Dimensions LxHxP mm | Power | Power supply | Output voltage | IP   | Code          |
|---------------------|-------|--------------|----------------|------|---------------|
| 225x51x65           | 70W   | 220-240Vac   | 48Vdc          | IP67 | <b>1E2320</b> |
| 225x51x65           | 150W  | 220-240Vac   | 48Vdc          | IP67 | <b>1E2321</b> |

Electronic ON-OFF power supply.  
Cable length 0.5m (IN and OUT).  
To be completed with Connection kit 1E4184.

| Dimensions LxHxP mm | Power | Power supply | Output voltage | IP   | Code            |
|---------------------|-------|--------------|----------------|------|-----------------|
| 225x36x60           | 60W   | 220-240Vac   | 48Vdc          | IP20 | <b>1T6917EL</b> |
| 240x49x60           | 130W  | 220-240Vac   | 48Vdc          | IP20 | <b>1T6916EL</b> |

Electronic ON-OFF power supply.  
To be completed with Connection kit 1E4184.

## Accessories

### Cable



| L mm | Code          |
|------|---------------|
| 500  | <b>1E4270</b> |
| 1000 | <b>1E4181</b> |
| 2000 | <b>1E4182</b> |
| 3000 | <b>1E4183</b> |

Connection cable complete with male/female connectors.

### Tool



| Code          |
|---------------|
| <b>1E4171</b> |

Microcrewdriver with hexagonal head (diameter 0.9mm) for wiring 1E4184 connection kit.

### Connector



| Code          |
|---------------|
| <b>1E4184</b> |

Connection kit 24/48V.  
Wire not included.  
Maximum cable diameter 7.5mm.  
To be used for lengths >3m.



| Code          |
|---------------|
| <b>1E2769</b> |

Linear connection box IP66/IP68.  
5 poles max. wire section 1.5mm<sup>2</sup>.  
Cable diameter range from 7 to 12mm.

*Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.*  
*Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).*

We reserve the right to make technical changes.

Targetti Sankey S.r.l.  
Via Pratese, 164  
50145 Firenze - Italy  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

CCIAA Firenze  
Share Capital:  
€ 500.000,00  
VAT N. (IT):  
01537660480  
R.E.A: FI-275656

**TARGETTI**

## 1E4131CA | IVY Multiple projector

### Adjustable LED 3x light module, powered at low voltage, to be installed into the installation profile

#### Connector



Code

**1E3184**

IP68 4-way cable connector (5 pole).

#### Control systems



Code

**1T8173CA**

Bridge DALI/Casambi: a fixture that allows fixtures equipped with mesh Bluetooth Casambi to interface with a traditional DALI system and to be adjusted by a DALI control unit.

Inside the usual DALI circuit it is possible to have a maximum of 64 cabled DALI and Casambi wireless devices.

It only works with Casambi Evolution networks.

The DALI Bridge is transparent in the DALI system, and therefore does not require an address.

There is no need for a power supply given that it is supplied directly by the DALI bus.

To provide IP68 rating to the fixture complete with code 1E3184.

LxHxP=40.4x14x36.3mm.

*Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.*

*Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).*

*We reserve the right to make technical changes.*

Targetti Sankey S.r.l.  
Via Pratese, 164  
50145 Firenze - Italy  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

CCIAA Firenze  
Share Capital:  
€ 500.000,00  
VAT N. (IT):  
01537660480  
R.E.A: FI-275656

# TARGETTI