


1E4156 | IVY Profile**Surface installation profile for ceiling/wall mounting needed for the installation of the lighting modules**

The figures on the drawing are expressed in mm.

MECHANICAL CHARACTERISTICS

Extruded aluminum profile protected with a layer of black anodization with a minimum thickness of 15 μ and powder painting in Ferrite grey color.

Colour and finish: Ferrite

Dimensions: L=1000mm

Weight: 2Kg

Version: SURFACE

NOTES

Linear connection joint already included in the packaging. Extruded plastic aesthetic cover available as accessory.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.


Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A.: FI-275656

TARGETTI

1E4156 | IVY Profile

Surface installation profile for ceiling/wall mounting needed for the installation of the lighting modules

Related codes**End Caps**

Colour	Code
--------	------

	1E4168
---	---------------

End caps made of 2 pieces.
For surface mounted installation profile.

Accessories**Mechanical connector**

Colour	Code
--------	------

	1E4176
---	---------------

L shaped joint planar.
For surface mounted installation profile.



Colour	Code
--------	------

	1E4177
---	---------------

L shaped joint concave.
For surface mounted installation profile.



Colour	Code
--------	------

	1E4178
---	---------------

L shaped joint convex.
For surface mounted installation profile.

Cover Panel

L mm	Colour	Code
------	--------	------

2000		1E4170
------	---	---------------

Extruded plastic cover.

Suspension

L mm	Colour	Code
------	--------	------

2000		2T0049
------	---	---------------

Suspension cable.
For indoor environment only.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.


Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

1E4156 | IVY Profile**Surface installation profile for ceiling/wall mounting needed for the installation of the lighting modules****Power Supply Kit**

L mm	Driver	Colour	Code
4000	ON-OFF	●	2T0048EL

Suspension installation kit: power cable complete with a painted polycarbonate rosette.

Max 0.6kW.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI