




1E4230 | IVY Profile

Surface installation profile for ceiling/wall mounting needed for the installation of the lighting modules

**MECHANICAL CHARACTERISTICS**

Extruded aluminum profile protected with a layer of black anodization with a minimum thickness of 15 μ and powder painting in white color.

Colour and finish: White

Dimensions: L=2000mm

Weight: 4Kg

Version: SURFACE

NOTES

Linear connection joint already included in the packaging. Extruded plastic aesthetic cover available as accessory.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.


Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A.: FI-275656

TARGETTI

1E4230 | IVY Profile


Surface installation profile for ceiling/wall mounting needed for the installation of the lighting modules

Related codes**End Caps**

Colour Code

○ **1E4234**


End caps made of 2 pieces.
For surface mounted installation profile.

Accessories**Mechanical connector**

Colour Code

○ **1E4236**

L shaped joint planar.
For surface mounted installation profile.



Colour Code

○ **1E4237**

L shaped joint concave.
For surface mounted installation profile.



Colour Code

○ **1E4238**

L shaped joint convex.
For surface mounted installation profile.

Cover Panel

L mm Colour Code

2000 ● **1E4170**

Extruded plastic cover.

Suspension

L mm Colour Code

2000 ● **2T0049**

Suspension cable.
For indoor environment only.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.


Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

1E4230 | IVY Profile**Surface installation profile for ceiling/wall mounting needed for the installation of the lighting modules****Power Supply Kit**

L mm	Driver	Colour	Code
4000	ON-OFF	○	1T5905EL

Suspension installation kit: power cable complete with a painted polycarbonate rosette.

Max 0.6kW.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI