


1E4250 | JEDI Projector RGBW

Powerful adjustable linear RGBW LED projector



The fixture's photometric values can be found on the following pages



The figures on the drawing are expressed in mm.

SOURCE

LED Multichip RGBW module with white 3000K.

Energy efficiency class: G

Nominal power: 22W

Nominal flux: See photometries

CCT nominal: See photometries

SDCM: 2

ILLUMINOTECHNICAL CHARACTERISTICS

Internal optical system composed of a primary cylindrical glass lens, a high reflectance anodised aluminium reflector and an integrated holographic filter.

Optic: HYBRID

Beam angles: GRZ

Optical efficiency: 79%

Fixture flux: See photometries

Luminous efficacy: See photometries

Photobiological safety: Compliant with RG1 low risk group

MECHANICAL CHARACTERISTICS

Extruded anodised aluminium 15µ body. Extra clear 4mm thick glass flat screen. Black polycarbonate driver box. The body of the fixture is adjustable and can be installed away from the mounting surface by sliding the brackets along a special guide.

Colour and finish: Aluminium

Dimensions: L=616mm

Weight: 3.7Kg

Degree of protection: IP66,IP67

Mechanical Resistance: IK08

ELECTRICAL CHARACTERISTICS

Integrated electronic power supply. Controlled using DMX-RDM protocols that allow to programme the fixture remotely (no dip-switch) using the DMX data line. Pass-through power supply with 1 meter cable and 3-pole IP68 connectors. Pass-through DMX line connection with 5-pole IP68 panel connectors. Programming the fixtures is done using the USB-RDM programmer that is available as an accessory.

Fixture Power: See photometries

Power supply: 220-240Vac 50/60Hz

Insulation Class: CLASS 1

Type of driver / Control: DMX RDM

Driver included: YES

Class F: YES

SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

Ambient temperature: -25°C / +35°C

INSTALLATION

To be completed with stainless steel fixed or adjustable brackets. The brackets can slide along the body of the fixture to be positioned according to installation needs.

NOTES

LMS Casambi wireless control available on request. Photometrics show the maximum emission values of fixtures. Uses the "Waterblock Smart" technical solution that involves resin coating the connection cables, limiting the risk of humidity reaching the driver or the fixture. 110-277Vac version available on request.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.


Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

1E4250 | JEDI Projector RGBW

Powerful adjustable linear RGBW LED projector



		H(m)	D1(m)	D2(m)	E _{max} (lx)		
		-	17°	80°			
Fixture Power	28W	1	0.30	1.67	2336		
Source Flux	1794lm	2	0.59	3.34	584		
Fixture Flux	1419lm	3	0.89	5.01	260		
Efficacy	52lm/W	4	1.18	6.69	146		
TS1773	I _{max} =1302cd/klm	I _{max}	2336cd	5	1.48	8.36	93




		H(m)	D1(m)	D2(m)	E _{max} (lx)		
		-	17°	80°			
Fixture Power	20W	1	0.30	1.67	1331		
Source Flux	1022lm	2	0.59	3.34	333		
Fixture Flux	808lm	3	0.89	5.01	148		
Efficacy	41lm/W	4	1.18	6.69	83		
TS1773	I _{max} =1302cd/klm	I _{max}	1331cd	5	1.48	8.36	53

RGBW

Fixture Power	28W
Nominal flux	1794lm
Fixture flux	1419lm
Luminous efficacy	52lm/W

RGB

Fixture Power	20W
Nominal flux	1022lm
Fixture flux	808lm
Luminous efficacy	41lm/W



	3000K	H(m)	D1(m)	D2(m)	E _{max} (lx)		
		-	17°	80°			
Fixture Power	7W	1	0.30	1.67	1138		
Source Flux	874lm	2	0.59	3.34	284		
Fixture Flux	691lm	3	0.89	5.01	126		
Efficacy	96lm/W	4	1.18	6.69	71		
TS1773	I _{max} =1302cd/klm	I _{max}	1138cd	5	1.48	8.36	46




		H(m)	D1(m)	D2(m)	E _{max} (lx)		
		-	17°	80°			
Fixture Power	5W	1	0.30	1.67	409		
Source Flux	314lm	2	0.59	3.34	102		
Fixture Flux	248lm	3	0.89	5.01	45		
Efficacy	47lm/W	4	1.18	6.69	26		
TS1773	I _{max} =1302cd/klm	I _{max}	409cd	5	1.48	8.36	16

WHITE


CCT nominal	3000K
Fixture Power	7W
Nominal flux	874lm
Fixture flux	691lm
Luminous efficacy	96lm/W

RED

Fixture Power	5W
Nominal flux	314lm
Fixture flux	248lm
Luminous efficacy	47lm/W



		H(m)	D1(m)	D2(m)	E _{max} (lx)		
		-	17°	80°			
Fixture Power	7W	1	0.30	1.67	838		
Source Flux	644lm	2	0.59	3.34	210		
Fixture Flux	509lm	3	0.89	5.01	93		
Efficacy	69lm/W	4	1.18	6.69	52		
TS1773	I _{max} =1302cd/klm	I _{max}	838cd	5	1.48	8.36	34



		H(m)	D1(m)	D2(m)	E _{max} (lx)		
		-	17°	80°			
Fixture Power	7W	1	0.30	1.67	164		
Source Flux	126lm	2	0.59	3.34	41		
Fixture Flux	100lm	3	0.89	5.01	18		
Efficacy	14lm/W	4	1.18	6.69	10		
TS1773	I _{max} =1302cd/klm	I _{max}	164cd	5	1.48	8.36	7

GREEN

Fixture Power	7W
Nominal flux	644lm
Fixture flux	509lm
Luminous efficacy	69lm/W

BLUE

Fixture Power	7W
Nominal flux	126lm
Fixture flux	100lm
Luminous efficacy	14lm/W

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656



1E4250 | JEDI Projector RGBW

Powerful adjustable linear RGBW LED projector

Related codes

Mounting System

Code
1E2752

Short bracket for wall installation (2 pieces).

Code
1E2753

Long bracket for wall installation (2 pieces).



Code
1E2754

Bracket for ceiling installation (2 pieces).

Accessories

End Caps



Code
1E2761

End cap with bracket for ceiling installation included.

Cover Panel

L mm	Code
616	1E3045

Side cover for ceiling installation.

L mm	Code
616	1E2755

Side cover for wall/cornice installation.

L mm	Code
616	1E2758

Anti-glare side cover.

Connector



Code
1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm².
Cable diameter range from 7 to 12mm.



Code
1E3184

IP68 4-way cable connector (5 pole).

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656



1E4250 | JEDI Projector RGBW

Powerful adjustable linear RGBW LED projector

Control systems



Code

1E2767

USB-RDM Programmer code.
DMX-RDM (Remote Device Management) address planner.
Used with the "RDM Targetti" software that can be downloaded for free from the Targetti website download section.
To be used with all RGBW products.
The USB-RDM programmer manages to direct DMX-RDM fixtures if there are no BUFFER or Splitter DMXs on the section.
Please refer to the instructions for more details.



Code

A077

my-SCENARIO Show Store.
Programmable DMX interface that integrates the latest innovations in lighting control in architectural and entertainment applications.
It features USB Type-C and Ethernet ports for programming and remote control.
The unit can be fully programmed with ESA Pro 2 software (available for Windows and Mac users) or via mobile applications such as Arcolis (available for iOS or Android devices).
It can be fully customised: pixel mapping, triggering management, patch configuration and much more.
The system offers great possibilities for the control of your lighting installation: multi zone control (allowing the management of up to 5 independent zones), extended triggers (time/date, Sunrise/Sunset, input ports, TCP/UDP commands), 16-bit channels management, full recovery after power loss, up to 99 total scenes, and 1024+ DMX channels.
The intuitive backlit keyboard comes with 10 preset buttons for a user friendly experience.




Code

1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
USB cable included.
To be used with all RGBW products.

Surge protector



Code

A013A

Surge protector compatible with CLASS I lighting fixtures.
Operating voltage 230-277Vac.
SPD type 2+3.
Max surge protection 10kV.
CLASS I
IP67

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI