



1E4252 | JEDI Projector RGBW

Powerful adjustable linear RGBW LED projector



The fixture's photometric values can be found on the following pages



The figures on the drawing are expressed in mm.

SOURCE

LED Multichip RGBW module with white 3000K.

Energy efficiency class: G

Nominal power: 33W

Nominal flux: See photometries

CCT nominal: See photometries

SDCM: 2

ILLUMINOTECHNICAL CHARACTERISTICS

Internal optical system composed of a primary cylindrical glass lens, a high reflectance anodised aluminium reflector and an integrated holographic filter.

Optic: HYBRID

Beam angles: FL

Optical efficiency: 75%

Fixture flux: See photometries

Luminous efficacy: See photometries

Photobiological safety: Compliant with RG1 low risk group

MECHANICAL CHARACTERISTICS

Extruded anodised aluminium 15µ body. Extra clear 4mm thick glass flat screen. Black polycarbonate driver box. The body of the fixture is adjustable and can be installed away from the mounting surface by sliding the brackets along a special guide.

Colour and finish: Aluminium

Dimensions: L=916mm

Weight: 4.5Kg

Degree of protection: IP66,IP67

Mechanical Resistance: IK08

ELECTRICAL CHARACTERISTICS

Integrated electronic power supply. Controlled using DMX-RDM protocols that allow to programme the fixture remotely (no dip-switch) using the DMX data line. Pass-through power supply with 1 meter cable and 3-pole IP68 connectors. Pass-through DMX line connection with 5-pole IP68 panel connectors. Programming the fixtures is done using the USB-RDM programmer that is available as an accessory.

Fixture Power: See photometries

Power supply: 220-240Vac 50/60Hz

Insulation Class: CLASS 1

Type of driver / Control: DMX RDM

Driver included: YES

Class F: YES

SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

Ambient temperature: -25°C / +35°C

INSTALLATION

To be completed with stainless steel fixed or adjustable brackets. The brackets can slide along the body of the fixture to be positioned according to installation needs.

NOTES

LMS Casambi wireless control available on request. Photometrics show the maximum emission values of fixtures. Uses the "Waterblock Smart" technical solution that involves resin coating the connection cables, limiting the risk of humidity reaching the driver or the fixture. 110-277Vac version available on request.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.


Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

1E4252 | JEDI Projector RGBW

Powerful adjustable linear RGBW LED projector



		H(m)	D1(m)	D2(m)	E _{max} (lx)		
		-	35°	88°			
Fixture Power	41W	1	0.63	1.94	1752		
Source Flux	2691lm	2	1.26	3.88	438		
Fixture Flux	2023lm	3	1.90	5.81	195		
Efficacy	49lm/W	4	2.53	7.75	109		
TS1771	I _{max} =651cd/klm	I _{max}	1752cd	5	3.16	9.69	70



		H(m)	D1(m)	D2(m)	E _{max} (lx)		
		-	35°	88°			
Fixture Power	30W	1	0.63	1.94	998		
Source Flux	1533lm	2	1.26	3.88	249		
Fixture Flux	1153lm	3	1.90	5.81	111		
Efficacy	39lm/W	4	2.53	7.75	62		
TS1771	I _{max} =651cd/klm	I _{max}	998cd	5	3.16	9.69	40

RGBW


Fixture Power	41W
Nominal flux	2691lm
Fixture flux	2023lm
Luminous efficacy	49lm/W

RGB

Fixture Power	30W
Nominal flux	1533lm
Fixture flux	1153lm
Luminous efficacy	39lm/W



	3000K	H(m)	D1(m)	D2(m)	E _{max} (lx)		
		-	35°	88°			
Fixture Power	11W	1	0.63	1.94	853		
Source Flux	1311lm	2	1.26	3.88	213		
Fixture Flux	986lm	3	1.90	5.81	95		
Efficacy	92lm/W	4	2.53	7.75	53		
TS1771	I _{max} =651cd/klm	I _{max}	853cd	5	3.16	9.69	34




		H(m)	D1(m)	D2(m)	E _{max} (lx)		
		-	35°	88°			
Fixture Power	8W	1	0.63	1.94	307		
Source Flux	471lm	2	1.26	3.88	77		
Fixture Flux	354lm	3	1.90	5.81	34		
Efficacy	44lm/W	4	2.53	7.75	19		
TS1771	I _{max} =651cd/klm	I _{max}	307cd	5	3.16	9.69	12

WHITE


CCT nominal	3000K
Fixture Power	11W
Nominal flux	1311lm
Fixture flux	986lm
Luminous efficacy	92lm/W

RED

Fixture Power	8W
Nominal flux	471lm
Fixture flux	354lm
Luminous efficacy	44lm/W



		H(m)	D1(m)	D2(m)	E _{max} (lx)		
		-	35°	88°			
Fixture Power	11W	1	0.63	1.94	629		
Source Flux	966lm	2	1.26	3.88	157		
Fixture Flux	726lm	3	1.90	5.81	70		
Efficacy	65lm/W	4	2.53	7.75	39		
TS1771	I _{max} =651cd/klm	I _{max}	629cd	5	3.16	9.69	25



		H(m)	D1(m)	D2(m)	E _{max} (lx)		
		-	35°	88°			
Fixture Power	11W	1	0.63	1.94	123		
Source Flux	189lm	2	1.26	3.88	31		
Fixture Flux	142lm	3	1.90	5.81	14		
Efficacy	13lm/W	4	2.53	7.75	8		
TS1771	I _{max} =651cd/klm	I _{max}	123cd	5	3.16	9.69	5

GREEN

Fixture Power	11W
Nominal flux	966lm
Fixture flux	726lm
Luminous efficacy	65lm/W

BLUE

Fixture Power	11W
Nominal flux	189lm
Fixture flux	142lm
Luminous efficacy	13lm/W

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656



1E4252 | JEDI Projector RGBW

Powerful adjustable linear RGBW LED projector

Related codes

Mounting System

Code
1E2752
Short bracket for wall installation (2 pieces).

Code
1E2753
Long bracket for wall installation (2 pieces).



Code
1E2754
Bracket for ceiling installation (2 pieces).


Accessories

End Caps




Code
1E2761
End cap with bracket for ceiling installation included.

Cover Panel



L mm	Code
916	1E3046
Side cover for ceiling installation.	

L mm	Code
916	1E2756
Side cover for wall/cornice installation.	



L mm	Code
916	1E2759
Anti-glare side cover.	

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656



1E4252 | JEDI Projector RGBW

Powerful adjustable linear RGBW LED projector

Connector



Code

1E2769

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm².
Cable diameter range from 7 to 12mm.



Code

1E3184

IP68 4-way cable connector (5 pole).

Control systems



Code

1E2767

USB-RDM Programmer code.
DMX-RDM (Remote Device Management) address planner.
Used with the "RDM Targetti" software that can be downloaded for free from the Targetti website download section.
To be used with all RGBW products.
The USB-RDM programmer manages to direct DMX-RDM fixtures if there are no BUFFER or Splitter DMXs on the section.
Please refer to the instructions for more details.



Code

A077

my-SCENARIO Show Store.
Programmable DMX interface that integrates the latest innovations in lighting control in architectural and entertainment applications.
It features USB Type-C and Ethernet ports for programming and remote control.
The unit can be fully programmed with ESA Pro 2 software (available for Windows and Mac users) or via mobile applications such as Arcolis (available for iOS or Android devices).
It can be fully customised: pixel mapping, triggering management, patch configuration and much more.
The system offers great possibilities for the control of your lighting installation: multi zone control (allowing the management of up to 5 independent zones), extended triggers (time/date, Sunrise/Sunset, input ports, TCP/UDP commands), 16-bit channels management, full recovery after power loss, up to 99 total scenes, and 1024+ DMX channels.
The intuitive backlit keyboard comes with 10 preset buttons for a user friendly experience.



Code

1T6499

myScenario Wall.
DMX controller with a glass touch sensitive screen for architectural applications.
It can control two different DMX universes (2x 512 channels).
Stand alone function or connected to a computer using a USB port.
Software for creating scenarios (that can be downloaded from the Targetti website) included.
It can manage 10 different lighting zones and 50 scenarios per zone.
The touch keys on the front make it possible to modify and recall programmed scenarios.
USB cable included.
To be used with all RGBW products.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com


CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

1E4252 | JEDI Projector RGBW

Powerful adjustable linear RGBW LED projector

Surge protector



Code

A013A

Surge protector compatible with CLASS I lighting fixtures.
Operating voltage 230-277Vac.
SPD type 2+3.
Max surge protection 10kV.
CLASS I
IP67

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI