

1E4287EL | IVY Stem mounted projector

Adjustable LED 1x light module with rigid suspension, powered at low voltage, to be installed into the installation profile



| | 3500K | H(m) | D(m) | Emax(lx) |
|---------------|------------------|------|--------|----------|
| | Ra90 | | 8° | |
| Fixture Power | 4W | 1 | 0.13 | 5789 |
| Source Flux | 362lm | 2 | 0.26 | 1447 |
| Fixture Flux | 235lm | 3 | 0.39 | 643 |
| Efficacy | 56lm/W | 4 | 0.53 | 362 |
| TS1719 | Imax=16015cd/klm | Imax | 5789cd | 5 |
| | | | 0.66 | 232 |



SOURCE

Emitter Ra90.
Energy efficiency class: F
Nominal power: 3,8W
Nominal flux: 362lm
Colour rendering index: 90
Rf: 94
Rg: 99
CCT nominal: 3500K
Lifetime (L80/B10): >50000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

NSP beam. Optics made of a lens in optical grade PMMA and a holographic diffusion filter.

Optic: LENS
Beam angles: NSP
Optical efficiency: 65%
Fixture flux: 235lm
Luminous efficacy: 56lm/W
Photobiological safety: Compliant with RG1 low risk group

MECHANICAL CHARACTERISTICS

Cylindrical aluminium body obtained through CNC machining process and protected with a layer of black anodization with a minimum thickness of 15µ. Powder painted Ferrite grey. Tempered extra clear front glass. Aluminium joint with locking system and rigid suspension in black anodized aluminium. Adjustability of the optical unit of 90° on the vertical plane (friction locking system) and 355° on the horizontal plane with the possibility of mechanical aiming locking through no tools system. Electronic components hosted inside a polymeric plastic box sealed by a silicone rubber gasket.

Colour and finish: Ferrite
Dimensions: L=148mm
Weight: 0.52Kg
Version: ON-OFF
Degree of protection: IP65

ELECTRICAL CHARACTERISTICS

Fixture Power: 4W
Power supply: 48Vdc
Insulation Class: CLASS 3
Class F: YES
Ambient temperature: -25°C / +35°C

INSTALLATION

Fast connection system of the modules through anodized aluminium clips. Free positioning all over the installation profile according to installation needs with mechanical lock through Hex Key. Designed for connection in series through H05RN-F (0.15m + 0.15m) cable completed with male/female miniaturised IP65 connectors.

NOTES

Electronic ON-OFF version.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
 Via Pratese, 164
 50145 Firenze - Italy
 Tel: +39 055 37911
 targetti.com
 targetti@targetti.com

CCIAA Firenze
 Share Capital:
 € 500.000,00
 VAT N. (IT):
 01537660480
 R.E.A.: FI-275656

TARGETTI

1E4287EL | IVY Stem mounted projector
Adjustable LED 1x light module with rigid suspension, powered at low voltage, to be installed into the installation profile

Related codes

Power Supply



| Driver | Colour | Code |
|--------|--------|---------------|
| ON-OFF | ● | 1E4169 |

48Vdc driver box (IP65).
L=450mm 90W.
Equipped with connection cable H05RN-F (0.15m + 0.15m) complete with male/female IP65 connectors for 220V and miniaturized female IP65 connector for 48V.



| Driver | Colour | Code |
|--------|--------|---------------|
| ON-OFF | ● | 1E4175 |

48Vdc driver box (IP65).
L=450mm 150W.
Equipped with connection cable H05RN-F (0.15m + 0.15m) complete with male/female IP65 connectors for 220V and miniaturized female IP65 connector for 48V.

Power Supply

| Dimensions LxHxP mm | Power | Power supply | Output voltage | IP | Code |
|---------------------|-------|--------------|----------------|------|---------------|
| 225x51x65 | 70W | 220-240Vac | 48Vdc | IP67 | 1E2320 |
| 225x51x65 | 150W | 220-240Vac | 48Vdc | IP67 | 1E2321 |

Electronic ON-OFF power supply.
Cable length 0.5m (IN and OUT).
To be completed with Connection kit 1E4184.

| Dimensions LxHxP mm | Power | Power supply | Output voltage | IP | Code |
|---------------------|-------|--------------|----------------|------|-----------------|
| 225x36x60 | 60W | 220-240Vac | 48Vdc | IP20 | 1T6917EL |
| 240x49x60 | 130W | 220-240Vac | 48Vdc | IP20 | 1T6916EL |

Electronic ON-OFF power supply.
To be completed with Connection kit 1E4184.

Accessories

Cable



| L mm | Code |
|------|---------------|
| 500 | 1E4270 |
| 1000 | 1E4181 |
| 2000 | 1E4182 |
| 3000 | 1E4183 |

Connection cable complete with male/female connectors.

Tool



| Code |
|---------------|
| 1E4171 |

Microcrewdriver with hexagonal head (diameter 0.9mm) for wiring 1E4184 connection kit.

Connector



| Code |
|---------------|
| 1E4184 |

Connection kit 24/48V.
Wire not included.
Maximum cable diameter 7.5mm.
To be used for lengths >3m.



| Code |
|---------------|
| 1E2769 |

Linear connection box IP66/IP68.
5 poles max. wire section 1.5mm².
Cable diameter range from 7 to 12mm.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

