


1T4499CA | HALL

Wall mounted fixture with indirect light emission for LED sources



	3000K	H(m)	D1(m)	D2(m)	E _{max} (lx)		
Ra80		121°	89°				
Fixture Power	40W	1	3.52	4.23	1588		
Source Flux	4908lm	2	7.04	8.47	397		
Fixture Flux	4235lm	3	10.56	12.70	176		
Efficacy	106lm/W	4	14.08	16.93	99		
TS892	I _{max} =487cd/klm	I _{max}	2388cd	5	17.60	21.17	64



SOURCE

Linear Low Power High Efficiency LED board Ra80.

Energy efficiency class: D

Nominal power: 36W

Nominal flux: 4908lm

Colour rendering index: 80

Rf: 82.9

Rg: 97

CCT nominal: 3000K

SDCM: 2

Lifetime (L80/B10): >50000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

A high reflectance anodised aluminium reflector.

Emission: ASYMMETRICAL

Optical efficiency: 86%

Fixture flux: 4235lm

Luminous efficacy: 106lm/W

Photobiological safety: Compliant with RG1 low risk group

MECHANICAL CHARACTERISTICS

Painted metal body. Diffusive protective screen.

Colour and finish: Florentine white

Weight: 3.6Kg

Degree of protection: IP20

ELECTRICAL CHARACTERISTICS

Casambi control system included in the LOF version. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

Fixture Power: 40W

Power supply: 220-240Vac 50/60Hz

Insulation Class: CLASS 1

Type of driver / Control: CASAMBI

Driver included: YES

Class F: YES

SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

Ambient temperature: 0°C / +25°C

NOTES

Design Daniel Bernard. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI