


**1T6088EL | THREESIXTY**

Circular LED fixture for ceiling, recessed, semi-recessed and wall mounted installations



		3000K	H(m)	D(m)	Emax(lx)
		Ra80		114°	
Fixture Power	48W	1	3.09	848	
Source Flux	4583lm	2	6.18	212	
Fixture Flux	2987lm	3	9.26	94	
Efficacy	62lm/W	4	12.35	53	
TS1515	I <sub>max</sub> =185cd/klm	I <sub>max</sub>	848cd	5	15.44

**SOURCE**

The LED Engine is made up of self-cooling circular boards. Tunable White version available on request.

**Energy efficiency class:** D, F

**Nominal power:** 43W

**Nominal flux:** 4583lm

**Colour rendering index:** 80

**Rf:** 82.9

**Rg:** 97

**CCT nominal:** 3000K

**SDCM:** 3

**Lifetime (L80/B10):** >50000h tq +25°C

**ILLUMINOTECHNICAL CHARACTERISTICS**

OPAL Direct + HALO effect Version: High luminance transmission and light diffusion opaline polycarbonate lower diffusive screen. Small indirect light component for a backlit effect.

**Emission:** OPAL + HALO

**Optical efficiency:** 65%

**Fixture flux:** 2987lm

**Luminous efficacy:** 62lm/W

**Photobiological safety:** Compliant with RG1 low risk group

**MECHANICAL CHARACTERISTICS**

Calendered extruded aluminium body.

**Colour and finish:** Deep black

**Dimensions:** D=384mm

**Weight:** 4.6Kg

**Degree of protection:** IP20 for recessed part

**Degree of protection:** IP40 for exposed part

**ELECTRICAL CHARACTERISTICS**

Integrated electronic ON-OFF power supply. Emergency Pack available on request. Equipped with a rapid connector for mains connection. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

**Fixture Power:** 48W

**Power supply:** 220-240Vac 50/60Hz

**Insulation Class:** CLASS 1

**Type of driver / Control:** ON-OFF

**Driver included:** YES

**Class F:** YES

**SAFE FLICKER:** PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

**Ambient temperature:** 0°C / +25°C

**INSTALLATION**

Polycarbonate fixing system is pre-set for ceiling or wall mounted installations. Recessed installation is possible using a special accessory to be ordered separately.

**NOTES**

110-277Vac version available on request.

**WARRANTY**

5 years.

**WARNING**

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.  
Via Pratese, 164  
50145 Firenze - Italy  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

CCIAA Firenze  
Share Capital:  
€ 500.000,00  
VAT N. (IT):  
01537660480  
R.E.A.: FI-275656


**TARGETTI**

## 1T6088EL | THREESIXTY

Circular LED fixture for ceiling, recessed, semi-recessed and wall mounted installations

### Related codes

#### Insertion Box



Cutout hole	Dimensions ØxH mm	Colour	Code
Ø450	460x165	●	<b>1T6402</b>

Casing for semi or completely recessed installation.

Load bearing outer casing measuring 384mm and 590mm.

Powder coated, spun aluminium body.

The outer casing attaches to the ceiling with pre-galvanised steel brackets.

Halo Version.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.  
Via Pratese, 164  
50145 Firenze - Italy  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

CCIAA Firenze  
Share Capital:  
€ 500.000,00  
VAT N. (IT):  
01537660480  
R.E.A: FI-275656

**TARGETTI**