


1T6263EL90 | THREESIXTY

Circular LED fixture for ceiling, recessed, semi-recessed and wall mounted installations



		4000K	H(m)	D(m)	E _{max} (lx)
		Ra90		114°	
Fixture Power	253W	1	3.09	5211	
Source Flux	26350lm	2	6.17	1303	
Fixture Flux	16542lm	3	9.26	579	
Efficacy	65lm/W	4	12.35	326	
TS1521	I _{max} =198cd/klm	I _{max}	5211cd	5	15.44

**SOURCE**

The LED Engine is made up of self-cooling circular boards. Tunable White version available on request.

Energy efficiency class: E

Nominal power: 225W

Nominal flux: 26350lm

Colour rendering index: 90

Rf: 89.8

Rg: 98.7

CCT nominal: 4000K

Lifetime (L80/B10): >50000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

OPAL Direct + HALO effect Version: High luminance transmission and light diffusion opaline polycarbonate lower diffusive screen. Small indirect light component for a backlit effect.

Emission: OPAL + HALO

Optical efficiency: 63%

Fixture flux: 16542lm

Luminous efficacy: 65lm/W

Photobiological safety: Compliant with RG1 low risk group

MECHANICAL CHARACTERISTICS

Calendered extruded aluminium body.

Colour and finish: Deep black

Dimensions: D=1150mm

Weight: 24Kg

Degree of protection: IP20 for recessed part

Degree of protection: IP40 for exposed part

ELECTRICAL CHARACTERISTICS

Integrated electronic ON-OFF power supply. Emergency Pack available on request. Equipped with a rapid connector for mains connection.

Fixture Power: 253W

Power supply: 220-240Vac 50/60Hz

Insulation Class: CLASS 1

Type of driver / Control: ON-OFF

Driver included: YES

Class F: YES

Ambient temperature: 0°C / +25°C

INSTALLATION

Polycarbonate fixing system is pre-set for ceiling or wall mounted installations. Recessed installation is possible using a special accessory to be ordered separately.

NOTES

110-277Vac version available on request.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A.: FI-275656

TARGETTI