


# 1T6270EL | THREESIXTY

## Circular LED fixture for suspension mounted installations



|               |                             | 3000K            | H(m)   | D(m) | E <sub>max</sub> (lx) |
|---------------|-----------------------------|------------------|--------|------|-----------------------|
|               |                             | Ra80             |        | 114° |                       |
| Fixture Power | 261W                        | 1                | 3.09   | 5761 |                       |
| Source Flux   | 33649lm                     | 2                | 6.17   | 1440 |                       |
| Fixture Flux  | 22227lm                     | 3                | 9.26   | 640  |                       |
| Efficacy      | 85lm/W                      | 4                | 12.35  | 360  |                       |
| TS1007        | I <sub>max</sub> =171cd/klm | I <sub>max</sub> | 5761cd | 5    | 15.43                 |



### SOURCE

The LED Engine is made up of self-cooling circular boards. Tunable White version available on request.

**Energy efficiency class:** D  
**Nominal power:** 234W  
**Nominal flux:** 33649lm  
**Colour rendering index:** 80  
**Rf:** 82.9  
**Rg:** 97  
**CCT nominal:** 3000K  
**SDCM:** 3  
**Lifetime (L80/B10):** >50000h tq +25°C

### ILLUMINOTECHNICAL CHARACTERISTICS

OPAL Direct/Indirect Version: High luminance transmission and light diffusion opaline polycarbonate lower diffusive screen. Diffused indirect emission LED Chip On Board.

**Emission:** UP-DOWN OPAL  
**Optical efficiency:** 66%  
**Fixture flux:** 22227lm  
**Luminous efficacy:** 85lm/W  
**Photobiological safety:** Compliant with RG1 low risk group

### MECHANICAL CHARACTERISTICS

Calendered extruded aluminium body.  
**Colour and finish:** Plaster white  
**Dimensions:** D=1150mm  
**Weight:** 24Kg  
**Degree of protection:** IP20 for recessed part  
**Degree of protection:** IP40 for exposed part

### ELECTRICAL CHARACTERISTICS

Integrated electronic ON-OFF power supply. Emergency Pack available on request. Equipped with a rapid connector for mains connection.

**Fixture Power:** 261W  
**Power supply:** 220-240Vac 50/60Hz  
**Insulation Class:** CLASS 1  
**Type of driver / Control:** ON-OFF  
**Driver included:** YES  
**Class F:** YES  
**Ambient temperature:** 0°C / +25°C

### INSTALLATION

Suspension installation is possible using a special accessory to be ordered separately.

### NOTES

DIRECT/INDIRECT VERSION: Fitted with separate switches. Three different light effects available: direct light, indirect light and mixed direct/indirect light. 110-277Vac version available on request.

### WARRANTY

5 years.

### WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.  
 Via Pratese, 164  
 50145 Firenze - Italy  
 Tel: +39 055 37911  
 targetti.com  
 targetti@targetti.com

CCIAA Firenze  
 Share Capital:  
 € 500.000,00  
 VAT N. (IT):  
 01537660480  
 R.E.A.: FI-275656

**TARGETTI**

**1T6270EL | THREESIXTY**  
**Circular LED fixture for suspension mounted installations**

**Related codes**

**Suspension**



| L mm | Colour | Code          |
|------|--------|---------------|
| 2000 |        | <b>1T6282</b> |
| 4000 |        | <b>1T6285</b> |

Suspension kit composed of 3 steel cables with an ABS control system.  
 Suspension kit compatible with ceiling or wall installations, even inclined.

**Power Supply Kit**



| Driver | Colour | Code            |
|--------|--------|-----------------|
| ON-OFF |        | <b>1T6288EL</b> |

Accessory for suspension installation composed of a canopy and 3 or 5 poles complete with a 4000mm power cable.

*Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
 Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).*

*We reserve the right to make technical changes.*

Targetti Sankey S.r.l.  
 Via Pratese, 164  
 50145 Firenze - Italy  
 Tel: +39 055 37911  
 targetti.com  
 targetti@targetti.com

CCIAA Firenze  
 Share Capital:  
 € 500.000,00  
 VAT N. (IT):  
 01537660480  
 R.E.A: FI-275656

