



1T9779EL | LABEL 6 - Ceiling
LED Ceiling-mounted fixture for direct light emission powered by mains voltage



4000K	H(m)	D(m)	E _{max} (lx)
Ra90		45°	
Fixture Power 10W	1	0.84	1809
Source Flux 1321lm	2	1.68	452
Fixture Flux 982lm	3	2.52	201
Efficacy 103lm/W	4	3.35	113
I _{max} 1809cd	5	4.19	72



The figures on the drawing are expressed in mm.

SOURCE

High efficiency Chip on Board LED Ra90. 2700K-3500K on request.
Energy efficiency class: E
Nominal power: 8,3W
Nominal flux: 1321lm
Colour rendering index: 90
Rf: 90
Rg: 98
CCT nominal: 4000K
Lifetime (L80/B10): >50000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

MWFL version - convex faceted highly reflective anodised aluminium precision optics, a holographic diffusion filter and a black silicone cut off ring.
Optic: REFLECTOR
Beam angles: MWFL
Optical efficiency: 74%
Fixture flux: 982lm
Luminous efficacy: 103lm/W
Photobiological safety: Compliant with RG1 low risk group

MECHANICAL CHARACTERISTICS

Cylindrical body in aluminum obtained through extrusion machining process and coated with powder paint.
Colour and finish: Deep black
Dimensions: D=59mm
Weight: 0.7Kg
Degree of protection: IP20

ELECTRICAL CHARACTERISTICS

Electronic ON-OFF version with the power supply integrated in the body of the fixture. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.
Fixture Power: 10W
Power supply: 220-240Vac 50/60Hz
Insulation Class: CLASS 2
Type of driver / Control: ON-OFF
Driver included: YES
Class F: YES
SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light
Ambient temperature: 0°C / +25°C

INSTALLATION

Kit with fixing plate for ceiling installation already included.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

*Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).*

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

