


## 2T0092DD | OZ Lighting module - Multiple

Fixed multiple magnetic LED light modules, powered at low voltage



		3000K	H(m)	D(m)	E <sub>max</sub> (lx)
		Ra90		19°	
Fixture Power	19W	1	0.34	10012	
Source Flux	2166lm	2	0.68	2503	
Fixture Flux	1770lm	3	1.02	1112	
Efficacy	94lm/W	4	1.36	626	
TS1835	I <sub>max</sub> =4623cd/klm	I <sub>max</sub>	10012cd	5	1.70
				400	



### SOURCE

High efficiency Chip on Board LED Ra90.

**Energy efficiency class:** F

**Nominal power:** 17W

**Nominal flux:** 2166lm

**Colour rendering index:** 90

**Rf:** 92

**Rg:** 101

**CCT nominal:** 3000K

**SDCM:** 2

**Lifetime (L80/B10):** >50000h tq +25°C

### ILLUMINOTECHNICAL CHARACTERISTICS

The spot optic system has a metallised polycarbonate precision optic, a holographic diffuser filter and a black polycarbonate frame. The light is suitable for installation in work environments UGR<19 (EN12464-1).

**Optic:** REFLECTOR

**Beam angles:** SP

**Optical efficiency:** 82%

**Fixture flux:** 1770lm

**Luminous efficacy:** 94lm/W

**Photobiological safety:** Compliant with RG1 low risk group

### MECHANICAL CHARACTERISTICS

White painted die-cast aluminium body. Multiple fixed light, 150x50mm.

**Colour and finish:** Plaster white

**Dimensions:** 50x150mm

**Weight:** 0.21Kg

**Version:** 3X DIGITAL DIMMING

**Degree of protection:** IP20

### ELECTRICAL CHARACTERISTICS

**Fixture Power:** 19W

**Power supply:** 48Vdc

**Insulation Class:** CLASS 3

**Class F:** YES

**Ambient temperature:** 0°C / +25°C

### INSTALLATION

Extremely rapid, versatile and simple mechanical and electrical coupling system using magnets which support the fixture on the Power Track and feed power inside the fixture on all versions.

### NOTES

Digital Dimming version. 110-277Vac version available on request.

### WARRANTY

5 years.

*Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.*

*Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).*

*We reserve the right to make technical changes.*

Targetti Sankey S.r.l.  
Via Pratese, 164  
50145 Firenze - Italy  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

CCIAA Firenze  
Share Capital:  
€ 500.000,00  
VAT N. (IT):  
01537660480  
R.E.A: FI-275656

**TARGETTI**