

2T0106CA | OZ Lighting module - Multiple

Fixed multiple magnetic LED light modules, powered at low voltage



		4000K	H(m)	D(m)	Emax(lx)	
		Ra90		19°		
Fixture Power	19W	1	0.34	10692		
Source Flux	2313lm	2	0.68	2673		
Fixture Flux	1890lm	3	1.02	1188		
Efficacy	101lm/W	4	1.36	668		
TS1835	Imax=4623cd/klm	Imax	10692cd	5	1.70	428



SOURCE

High efficiency Chip on Board LED Ra90.

Energy efficiency class: F

Nominal power: 17W

Nominal flux: 2313lm

Colour rendering index: 90

Rf: 90

Rg: 98

CCT nominal: 4000K

SDCM: 2

Lifetime (L80/B10): >50000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

The spot optic system has a metallised polycarbonate precision optic, a holographic diffuser filter and a black polycarbonate frame. The light is suitable for installation in work environments UGR<19 (EN12464-1).

Optic: REFLECTOR

Beam angles: SP

Optical efficiency: 82%

Fixture flux: 1890lm

Luminous efficacy: 101lm/W

Photobiological safety: Compliant with RG1 low risk group

MECHANICAL CHARACTERISTICS

Black painted die-cast aluminium body. Multiple fixed light, 150x50mm.

Colour and finish: Deep black

Dimensions: 50x150mm

Weight: 0.21Kg

Version: 3X CASAMBI

Degree of protection: IP20

ELECTRICAL CHARACTERISTICS

Fixture Power: 19W

Power supply: 48Vdc

Insulation Class: CLASS 3

Class F: YES

Ambient temperature: 0°C / +25°C

INSTALLATION

Extremely rapid, versatile and simple mechanical and electrical coupling system using magnets which support the fixture on the Power Track and feed power inside the fixture on all versions.

NOTES

Integrated Casambi control system (Casambi Ready). DALI control system available using a special accessory. 110-277Vac version available on request.

WARRANTY

5 years.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI