



E024BFL924BA | CATIRPEL

Modular low voltage outdoor system. Thanks to its flexibility, it can be installed in contexts of curved and irregular surfaces



		2400K	H(m)	D(m)	E _{max} (lx)	
		Ra90		25°		
	Fixture Power	6W	1	0.45	688	
	Source Flux	508lm	2	0.90	172	
	Fixture Flux	192lm	3	1.36	76	
	Efficacy	35lm/W	4	1.81	43	
TS1950	I _{max} =1355cd/klm	I _{max}	688cd	5	2.26	28

**SOURCE**

High efficiency Chip on Board LED Ra90 available in four colour temperatures.

Energy efficiency class: F

Nominal power: 1X4,7W

Nominal flux: 508lm

Colour rendering index: 90

CCT nominal: 2400K

Lifetime (L80/B10): >50000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

Louvre - FL version: optic composed of an optical grade PMMA lens, a holographic diffusing filter and a black painted aluminium anti-glare grid with a honeycomb structure. Optical accessories available to control the light beam.

Optic: LENS

Beam angles: FL

Optical efficiency: 38%

Fixture flux: 192lm

Luminous efficacy: 35lm/W

Photobiological safety: Compliant with RG1 low risk group

MECHANICAL CHARACTERISTICS

It's made of adjustable projectors that can be oriented in multiple directions in space, thanks to a mechanical connection made through spherical joints. Cylindrical aluminium bodies obtained through CNC machining process and protected with a layer of black anodization with a minimum thickness of 15µ. Joint body in die-cast aluminum with cataphoresis treatment. Tempered extra clear front glass. Flexibility of the optical bodies by ±110° on the vertical plane and mechanical locking. Flexibility of the chain with respect to the contact surface of ±45°. Minimum achievable curvature radius of 95mm with an angle of 45° between projectors. IP67 in-out connectors (in Nylon).

Colour and finish: Black anodized

Dimensions: L=290mm

Weight: 0.24Kg

Version: 1X END - LOUVRE

Degree of protection: IP66, IP67

Mechanical Resistance: IK06

ELECTRICAL CHARACTERISTICS

To be completed with remote driver. Connection cables and 3-way connector available as accessories. Complete with through wiring. Refer to installation manual for the maximum system distances.

Fixture Power: 6W

Power supply: 24Vdc

Insulation Class: CLASS 3

Class F: YES

SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

Ambient temperature: -25°C / +35°C

INSTALLATION

Dead end with external cable (0.15m) completed with male miniaturised IP67 connector. Accessories available for multiple installation modes.

NOTES

The photometrics refer to individual projectors. Values related to the power consumption of the fixture do not take into account the consumption of the accessory driver, which depends on the choice of driver.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Non-replaceable control gear.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

E024BFL924BA | CATIRPEL

Modular low voltage outdoor system. Thanks to its flexibility, it can be installed in contexts of curved and irregular surfaces

Related codes**Power Supply**

	Colour	Code
		A015BT

24Vdc driver box (IP67).

L=250mm 80W.

Provided with IP67 male/female connectors for 220-240V and IP67 miniaturized female connector for 24V.

Dimensions LxHxP mm	Power	Power supply	Output voltage	IP	Code
230x87x43	100W	220-240Vac	24Vdc	IP67	1T3587
238x42x67	200W	220-240Vac	24Vdc	IP67	1T3588

Electronic ON-OFF power supply.

Accessories**Screen**

	Colour	Code
		A031BA

Cylindrical screen.

Aluminium with black anodizing treatment.



	Colour	Code
		A017BA

Asymmetric screen.

Aluminium with black anodizing treatment.

Grid

	Colour	Code
		A032BA

Anti-glare louver.

The central elements can be adjusted +/- 360° for a perfect glare control.

Aluminium with black anodizing treatment.

Holder Ring

	Colour	Code
		A033BA

Holder ring.

Aluminium with black anodizing treatment.

Filter

	Code
	A034

Blade of light filter.

To be used with holder ring A033.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

E024BFL924BA | CATIRPEL

Modular low voltage outdoor system. Thanks to its flexibility, it can be installed in contexts of curved and irregular surfaces

Bracket



Colour Code



A019BT



Colour Code



A020BT

Bracket for installation on surfaces.
Powder coated stainless steel.

Bracket for installation on trees.
To be completed with accessory strap A023.
Powder coated stainless steel.

Mounting System



L mm Code

2000

A023

Strap for tree bracket (tree installation).



L mm H mm P mm Colour Code

25

162

25



A021BT

Earthspike.
Powder coated stainless steel.



H mm Colour Code

20



A022BA

Cylindrical spacer.
Aluminium with black anodizing treatment.



H mm Colour Code

20



A055BA

Cylindrical spacer for cable installation (not supplied).
Aluminium with black anodizing treatment.

Cable



L mm Code

1000

A026

2000

A027

3000

A028

6000

A078

Connection cable.

End Caps



Code

A029

End cap for miniaturized female connector.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value, tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

E024BFL924BA | CATIRPEL**Modular low voltage outdoor system. Thanks to its flexibility, it can be installed in contexts of curved and irregular surfaces****Cable**

Code

A030

Connection kit for remote driver.

Connector

Code

A024

3 ways connector (1IN-2OUT).

Control systems

Code

1T6581

Dimmer for 12-24Vdc constant voltage LED driver.
1-10V/DALI control input.
IP20

Code

1E3048

IP67 wireless control unit with DALI interface.
It generates a local DALI2 bus, enabling a direct connection to a DALI interface LED driver.
The module can only be used in a closed system and cannot be connected to an existing DALI network.
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 5.0 technology.
The devices automatically create an adaptive, robust, and reliable wireless mesh network, allowing for the easy and efficient management of a high number of fixtures. The control unit is preset to the DALI 1CH profile, meaning the device can control a single DALI driver with broadcast commands.
In addition to the DALI broadcast, other operating modes are available, such as:

- Button (normally open)
- Control unit 0/1-10V
- Control unit DALI Tunable White DT8
- Presence sensor



Code

1E4369

IP67 Extender for wireless control of LED driver with dimming DALI interface based on Casambi technology.

It has a DALI2 output with the capacity to control up to 40 lighting fixtures.

With the addition of a further external BUS DALI power supply it is possible to control up to 64 fixtures.

IP67 Extender is preset to the DALI broadcast profile, meaning all the luminaires connected to it are dimmable at the same level.

In addition to the DALI broadcast other operating modes are available, such as:

- EXTENDER DALI 8CH
- EXTENDER DALI Tunable White
- EXTENDER DALI 4CH
- EXTENDER DALI DT8 Tunable White

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI