



T001MW940D2DB | LOGICO EASY System 37 - OPAL

LED luminaire for ceiling or suspended system installation. Linear module



	4000K	H(m)	D(m)	Emax(lx)		
	Ra90	113°				
	Fixture Power	58W	1	3.00	1254	
	Source Flux	3613lm	2	6.00	314	
	Fixture Flux	3613lm	3	9.00	139	
	Efficacy	62lm/W	4	12.00	78	
6000843a	I _{max} =347cd/klm	I _{max}	1255cd	5	15.00	50



The figures on the drawing are expressed in mm.

SOURCE

LED Engine made of linear LED boards Ra90.

Energy efficiency class: E

Nominal power: 50W

Nominal flux: 3613lm

Colour rendering index: 90

Rf: 92

Rg: 101

CCT nominal: 4000K

Lifetime (L80/B10): 100000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

Direct emission. Diffused light - OPAL optic: optical system made of a steel reflector with white polymer coating and a closing diffuser screen in opal anti-glare polycarbonate supplied in unrollable reels and available as a related code.

Emission: DIRECT

Optic: REFLECTOR

Optical efficiency: 100%

Fixture flux: 3613lm

Luminous efficacy: 62lm/W

Photobiological safety: Compliant with RG0 exempt risk group

MECHANICAL CHARACTERISTICS

Painted extruded aluminium body with 37mm section. Upper closing screen in black PVC.

Colour and finish: Black

Dimensions: L=2916mm

Weight: 6Kg

Version: LINEAR

Degree of protection: IP40

Mechanical Resistance: IK02

ELECTRICAL CHARACTERISTICS

Integrated electronic DALI2 driver. "Easy Connection" system for a quick connection between the modules of the system thanks to the pre-assembled plug/socket connection elements. Complete with 1.5mm² section through wiring allowing to reach a maximum length of 18 meters. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 15% in DC.

Fixture Power: 58W

Power supply: 220-240Vac 50/60Hz

Insulation Class: CLASS 1

Type of driver / Control: DALI2

Driver included: YES

Class F: YES

SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

Ambient temperature: 0°C / +25°C

Relative humidity UR: <85%

INSTALLATION

To be completed with polycarbonate end caps, mounting systems for surface or suspended application and terminal block for connection to the power line.

NOTES

For angular configurations L light modules or the L blind joint accessory are available.

REGULATIONS AND CERTIFICATIONS

CE.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

T001MW940D2DB | LOGICO EASY System 37 - OPAL

LED luminaire for ceiling or suspended system installation. Linear module

Related codes

Screen



	Dimensions	Code
	L=6m	A002SL1
	L=9m	A002SL2
	L=15m	A002SL3

OPAL screen (Direct Emission).
For LOGICO EASY System 37 - OPAL.

Accessories

Electrical Connector



	Driver	Colour	Code
	DALI2	●	A014SD2B

L-shaped blind joint.
Sizes 808x808x80mm.
For LOGICO EASY System 37.

End Caps



	Colour	Code
	●	A003S2B

End caps (2 pieces).
For LOGICO EASY System 37 - OPAL.

Canopy



	Colour	Code
	●	A004B

Canopy with 5 poles terminal block.
Feeding cable not included.

Cover Panel



	Colour	Code
	●	A005SB

Joint for screens.
To be used for configurations longer than 15 meters.
For LOGICO EASY System 37.

Bracket



	Code
	A006S

Bracket for ceiling installation (2 pieces).
Two brackets needed for each lighting module.
For LOGICO EASY 37.



	Code
	A007S

Bracket with adjustment system for suspended installation (2 pieces).
Two brackets needed for each lighting module.
For LOGICO EASY 37.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

T001MW940D2DB | LOGICO EASY System 37 - OPAL

LED luminaire for ceiling or suspended system installation. Linear module

Suspension



	Version	Code
	L=6m	A008T
	L=5m	A008U
	L=4m	A008V
	L=3m	A008W
	L=2m	A008X
	L=1m	A008Y
	L=0,5m	A008Z

Suspension cable (2 pieces).

Terminal Box



	Version	Code
	3 Poli ON-OFF	A009Z

Terminal block (plug/socket).

One for each power supply.

A009Z - For LOGICO EASY 37 | 57 | 100.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI