



T003BW930ELPW | LOGICO EASY System 37 - UGR19

Linear LED fixture for ceiling mounted or suspension system installation



	3000K	H(m)	D1(m)	D2(m)	E _{max} (lx)
Ra90			66°	64°	
Fixture Power	88W	1	1.29	1.26	3531
Source Flux	7958lm	2	2.58	2.52	883
Fixture Flux	7959lm	3	3.86	3.78	392
Efficacy	90lm/W	4	5.15	5.04	221
G0347A I _{max} =502cd/klm	I _{max}	5	6.44	6.30	141



The figures on the drawing are expressed in mm.

SOURCE

LED Engine made of linear LED boards Ra90.

Energy efficiency class: D, E

Nominal power: 78W

Nominal flux: 7958lm

Colour rendering index: 90

Rf: 92

Rg: 101

CCT nominal: 3000K

Lifetime (L80/B10): 100000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

Direct/indirect emission. Controlled light. UGR19 Optics: optical system made of lenses with differentiated facets for optimizing the direction of the luminous flux and cellular optics in white anti-glare polycarbonate (UGR<19 and L65<1500 cd/m² EN-12464-1).

Emission: DIRECT/INDIRECT

Optic: CELLULAR

Optical efficiency: 100%

Fixture flux: 7958lm

Luminous efficacy: 90lm/W

Photobiological safety: Compliant with RG0 exempt risk group

MECHANICAL CHARACTERISTICS

Painted extruded aluminium body with 37mm section. Upper closing screen in translucent polycarbonate.

Colour and finish: White

Dimensions: L=2799mm

Weight: 6.3Kg

Version: LINEAR

Degree of protection: IP40

Mechanical Resistance: IK02

ELECTRICAL CHARACTERISTICS

Integrated electronic ON-OFF driver. "Easy Connection" system for a quick connection between the modules of the system thanks to the pre-assembled plug/socket connection elements. Complete with 1.5mm² section through wiring allowing to reach a maximum length of 18 meters. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

Fixture Power: 88W

Power supply: 220-240Vac 50/60Hz

Insulation Class: CLASS 1

Type of driver / Control: ON-OFF

Driver included: YES

Class F: YES

SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

Ambient temperature: 0°C / +25°C

Relative humidity UR: <85%

INSTALLATION

To be completed with polycarbonate end caps, mounting systems for surface or suspended application and terminal block for connection to the power line.

NOTES

For angular configurations the L blind joint accessory is available.

REGULATIONS AND CERTIFICATIONS

CE.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

T003BW930ELPW | LOGICO EASY System 37 - UGR19
 Linear LED fixture for ceiling mounted or suspension system installation

Accessories

Electrical Connector



Driver	Colour	Code
ON-OFF	○	A014SELW

L-shaped blind joint.
 Sizes 808x808x80mm.
 For LOGICO EASY System 37.

End Caps



Colour	Code
○	A003S1W

End caps (2 pieces).
 For LOGICO EASY System 37 - UGR19.

Canopy



Colour	Code
○	A004W

Canopy with 5 poles terminal block.
 Feeding cable not included.

Bracket



Code
A007S

Bracket with adjustment system for suspended installation (2 pieces).
 Two brackets needed for each lighting module.
 For LOGICO EASY 37.

Suspension



Version	Code
L=6m	A008T
L=5m	A008U
L=4m	A008V
L=3m	A008W
L=2m	A008X
L=1m	A008Y
L=0,5m	A008Z

Suspension cable (2 pieces).

Terminal Box



Version	Code
3 Poli ON-OFF	A009Z

Terminal block (plug/socket).
 One for each power supply.
A009Z - For LOGICO EASY 37 | 57 | 100.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
 Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
 Via Pratese, 164
 50145 Firenze - Italy
 Tel: +39 055 37911
 targetti.com
 targetti@targetti.com

CCIAA Firenze
 Share Capital:
 € 500.000,00
 VAT N. (IT):
 01537660480
 R.E.A.: FI-275656

