

## T009BW830D2DB | LOGICO EASY System 57 - OPAL / UGR19

### LED luminaire for ceiling or suspended system installation. Emergency linear module



The fixture's photometric values can be found on the following pages



The figures on the drawing are expressed in mm.

#### SOURCE

LED Engine made of linear LED boards Ra80.

**Energy efficiency class:** D

**Nominal power:** 90W

**Nominal flux:** See photometries

**Colour rendering index:** 80

**Rf:** 84

**Rg:** 95

**CCT nominal:** 3000K

**Lifetime (L80/B10):** 100000h tq +25°C

#### ILLUMINOTECHNICAL CHARACTERISTICS

Direct/indirect emission in two effect variants: diffused light - OPAL optics - and controlled light - UGR19 optics. Diffused light - OPAL optic: optical system made of a steel reflector with white polymer coating and a closing diffuser screen in opal anti-glare polycarbonate supplied in unrollable reels and available as a related code. Controlled light - UGR19 optic: optical system made of a steel reflector with white polymer coating and UGR closing diffuser screen supplied in unrollable reels and available as a related code (UGR<19 and L65<3000 cd/m<sup>2</sup> EN-12464-1).

**Emission:** DIRECT/INDIRECT

**Optic:** REFLECTOR

**Optical efficiency:** 100%

**Fixture flux:** See photometries

**Emergency fixture flux BLF:** 10% (Direct emission)

**Luminous efficacy:** See photometries

**Photobiological safety:** Compliant with RG0 exempt risk group

#### MECHANICAL CHARACTERISTICS

Painted extruded aluminium body with 57mm section. Upper closing screen in translucent polycarbonate.

**Colour and finish:** Black

**Dimensions:** L=2916mm

**Weight:** 7.335Kg

**Version:** LINEAR

**Degree of protection:** IP40

**Mechanical Resistance:** IK02

#### ELECTRICAL CHARACTERISTICS

Integrated electronic DALI2 driver. "Easy Connection" system for a quick connection between the modules of the system thanks to the pre-assembled plug/socket connection elements. Preset for through wiring allowing to reach a maximum length of 18 meters. Equipped with emergency pack - permanent emergency (1h autonomy and 24h recharge).

**Fixture Power:** 101W

**Power supply:** 220-240Vac 50/60Hz

**Insulation Class:** CLASS 1

**Type of driver / Control:** DALI2 (EMERGENCY VERSION)

**Driver included:** YES

**Class F:** YES

**SAFE FLICKER:** PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

**Ambient temperature:** 0°C / +25°C

**Relative humidity UR:** <85%

#### INSTALLATION

To be completed with polycarbonate end caps, mounting systems for surface or suspended application and terminal block for connection to the power line.

#### NOTES

Casambi control system available using a dedicated accessory. Consult factory to verify the quantity of DALI drivers installed. For angular configurations L light modules and the L blind joint accessory are available. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

#### REGULATIONS AND CERTIFICATIONS

CE.

#### WARRANTY

5 years.

#### WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).


We reserve the right to make technical changes.


Targetti Sankey S.r.l.  
Via Pratese, 164  
50145 Firenze - Italy  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

CCIAA Firenze  
Share Capital:  
€ 500.000,00  
VAT N. (IT):  
01537660480  
R.E.A.: FI-275656

**TARGETTI**

**T009BW830D2DB | LOGICO EASY System 57 - OPAL / UGR19**  
**LED luminaire for ceiling or suspended system installation. Emergency linear module**

	3000K	H(m)	D(m)	Emax(lx)		
	Ra80		111°			
	Fixture Power	101W	1	2.90	1423	
	Source Flux	10620lm	2	5.80	356	
	Fixture Flux	10620lm	3	8.70	158	
	Efficacy	106lm/W	4	11.60	89	
G0300A	I <sub>max</sub> =222cd/klm	I <sub>max</sub>	2359cd	5	14.49	57

	3000K	H(m)	D1(m)	D2(m)	Emax(lx)		
	Ra80		83°	89°			
	Fixture Power	101W	1	1.78	1.97	2156	
	Source Flux	10565lm	2	3.56	3.94	539	
	Fixture Flux	10566lm	3	5.33	5.91	240	
	Efficacy	105lm/W	4	7.11	7.88	135	
G0300	I <sub>max</sub> =226cd/klm	I <sub>max</sub>	2384cd	5	8.89	9.85	86

**OP**

Nominal flux	10620lm
Fixture flux	10620lm
Luminous efficacy	106lm/W

**UGR**

Nominal flux	10565lm
Fixture flux	10565lm
Luminous efficacy	105lm/W

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
 Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

Targetti Sankey S.r.l.  
 Via Pratese, 164  
 50145 Firenze - Italy  
 Tel: +39 055 37911  
 targetti.com  
 targetti@targetti.com

CCIAA Firenze  
 Share Capital:  
 € 500.000,00  
 VAT N. (IT):  
 01537660480  
 R.E.A.: FI-275656



We reserve the right to make technical changes.

**T009BW830D2DB | LOGICO EASY System 57 - OPAL / UGR19**  
**LED luminaire for ceiling or suspended system installation. Emergency linear module**

**Related codes**

**Screen**



Dimensions	Code
L=6m	<b>A001ML1</b>
L=9m	<b>A001ML2</b>
L=15m	<b>A001ML3</b>

UGR19 screen (Direct Emission).  
 For LOGICO EASY System 57 - UGR19.



Dimensions	Code
L=6m	<b>A002ML1</b>
L=9m	<b>A002ML2</b>
L=15m	<b>A002ML3</b>

OPAL screen (Direct Emission).  
 For LOGICO EASY System 57 - OPAL.

**Accessories**

**Electrical Connector**



Driver	Colour	Code
DALI2	●	<b>A014MD2B</b>

L-shaped blind joint.  
 Sizes 818x818x80mm.  
 For LOGICO EASY System 57.

**End Caps**



Colour	Code
●	<b>A003M2B</b>

End caps (2 pieces).  
 For LOGICO EASY System 57 - OPAL / UGR19.

**Canopy**



Colour	Code
●	<b>A004B</b>

Canopy with 5 poles terminal block.  
 Feeding cable not included.

**Cover Panel**



Colour	Code
●	<b>A005MB</b>

Joint for screens.  
 To be used for configurations longer than 15 meters.  
 For LOGICO EASY System 57.

**Bracket**



Code
<b>A007M</b>

Bracket with adjustment system for suspended installation (2 pieces).  
 Two brackets needed for each lighting module.  
 For LOGICO EASY 57.

**Suspension**



Version	Code
L=6m	<b>A008T</b>
L=5m	<b>A008U</b>
L=4m	<b>A008V</b>
L=3m	<b>A008W</b>
L=2m	<b>A008X</b>
L=1m	<b>A008Y</b>
L=0,5m	<b>A008Z</b>

Suspension cable (2 pieces).

*Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.*  
 Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.  
 Via Pratese, 164  
 50145 Firenze - Italy  
 Tel: +39 055 37911  
 targetti.com  
 targetti@targetti.com

CCIAA Firenze  
 Share Capital:  
 € 500.000,00  
 VAT N. (IT):  
 01537660480  
 R.E.A: FI-275656



## T009BW830D2DB | LOGICO EASY System 57 - OPAL / UGR19 LED luminaire for ceiling or suspended system installation. Emergency linear module

### Terminal Box



Version	Code
---------	------

5 Poli DALI	<b>A009X</b>
-------------	--------------

Terminal block (plug/socket).  
One for each power supply.  
**A009X** - For LOGICO EASY 57 I 100.

### Control systems



Code
------

<b>1T5349</b>
---------------

IP20 wireless control unit with DALI interface.  
It generates a local DALI2 bus, enabling a direct connection to a DALI interface LED driver.  
The module can only be used in a closed system and cannot be connected to an existing DALI network.  
The module is wireless controlled using a Casambi app for smartphones and tablets using Bluetooth 5.0 technology.  
The devices automatically create an adaptive, robust, and reliable wireless mesh network, allowing for the easy and efficient management of a high number of fixtures.  
The control unit is preset to the DALI 1CH profile, meaning the device can control a single DALI driver with broadcast commands.  
In addition to the DALI broadcast, other operating modes are available, such as:

- Button (normally open)
- Control unit 0/1-10V
- Control unit DALI Tunable White DT8
- Presence sensor



Code
------

<b>2T0131</b>
---------------

IP20 Extender for wireless control of LED driver with dimming DALI (or 1-10V) interface based on Casambi technology.  
It has a DALI2 output with the capacity to control up to 40 lighting fixtures.  
With the addition of a further external BUS DALI power supply it is possible to control up to 64 fixtures.  
IP20 Extender is preset to the DALI broadcast profile, meaning all the luminaires connected to it are dimmable at the same level.  
In addition to the DALI broadcast other operating modes are available, such as:

- EXTENDER DALI 8CH
- EXTENDER DALI Tunable White
- EXTENDER 0/1-10V
- EXTENDER DALI 4CH
- EXTENDER DALI DT8 Tunable White

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.  
Via Pratese, 164  
50145 Firenze - Italy  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

CCIAA Firenze  
Share Capital:  
€ 500.000,00  
VAT N. (IT):  
01537660480  
R.E.A.: FI-275656

**TARGETTI**