



T010BV830ELDB | LOGICO EASY System 57 - OPAL / UGR19

LED luminaire for ceiling or suspended system installation. L module



The fixture's photometric values
can be found on the following pages



SOURCE

LED Engine made of linear LED boards Ra80.

Energy efficiency class: D

Nominal power: 2x21W

Nominal flux: See photometries

Colour rendering index: 80

Rf: 84

Rg: 95

CCT nominal: 3000K

Lifetime (L80/B10): 100000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

Direct/indirect emission in two effect variants: diffused light - OPAL optics - and controlled light - UGR19 optics. Diffused light - OPAL optic: optical system made of a steel reflector with white polymer coating and a closing diffuser screen in opal anti-glare polycarbonate supplied in unrollable reels and available as a related code. Controlled light - UGR19 optic: optical system made of a steel reflector with white polymer coating and UGR closing diffuser screen supplied in unrollable reels and available as a related code (UGR<19 and L65<3000 cd/m² EN-12464-1).

Emission: DIRECT/INDIRECT

Optic: REFLECTOR

Optical efficiency: 100%

Fixture flux: See photometries

Luminous efficacy: See photometries

Photobiological safety: Compliant with RG0 exempt risk group

MECHANICAL CHARACTERISTICS

Painted extruded aluminium body with 57mm section. Upper closing screen in translucent polycarbonate.

Colour and finish: Black

Dimensions: AxB=818x818mm

Weight: 3.45Kg

Version: L CONNECTOR

Degree of protection: IP40

Mechanical Resistance: IK02

ELECTRICAL CHARACTERISTICS

Integrated electronic ON-OFF driver. "Easy Connection" system for a quick connection between the modules of the system thanks to the pre-assembled plug/socket connection elements. Preset for through wiring allowing to reach a maximum length of 18 meters. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

Fixture Power: 2x24W

Power supply: 220-240Vac 50/60Hz

Insulation Class: CLASS 1

Type of driver / Control: ON-OFF

Driver included: YES

Class F: YES

SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

Ambient temperature: 0°C / +25°C

Relative humidity UR: <85%

INSTALLATION

To be completed with polycarbonate end caps, mounting systems for surface or suspended application and terminal block for connection to the power line.

NOTES

Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

REGULATIONS AND CERTIFICATIONS

CE.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).


We reserve the right to make technical changes.


Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

T010BV830ELDB | LOGICO EASY System 57 - OPAL / UGR19 **LED luminaire for ceiling or suspended system installation. L module**

	3000K	H(m)	D(m)	Emax(lx)		
	Ra80		111°			
	Fixture Power	24W	1	2.90	321	
	Source Flux	2395lm	2	5.80	80	
	Fixture Flux	2395lm	3	8.70	36	
	Efficacy	102lm/W	4	11.60	20	
	G0300A	I _{max} =222cd/klm	I _{max}	532cd	5	14.49

	3000K	H(m) D1(m) D2(m) Emax(lx)					
	Ra80	83° 89°					
	Fixture Power	24W	1	1.78	1.97	486	
	Source Flux	2382lm	2	3.56	3.94	122	
	Fixture Flux	2382lm	3	5.33	5.91	54	
	Efficacy	101lm/W	4	7.11	7.88	30	
	G0300	I _{max} =226cd/klm	I _{max}	538cd	5	8.89	9.85

OP

Nominal flux	2x4790lm
Fixture flux	2x2395lm
Luminous efficacy	204lm/W

UGR

Nominal flux	2x4763lm
Fixture flux	2x2382lm
Luminous efficacy	203lm/W

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

T010BV830ELDB | LOGICO EASY System 57 - OPAL / UGR19

LED luminaire for ceiling or suspended system installation. L module

Related codes

Screen



	Dimensions	Code
	L=6m	A001ML1
	L=9m	A001ML2
	L=15m	A001ML3

UGR19 screen (Direct Emission).
For LOGICO EASY System 57 - UGR19.



	Dimensions	Code
	L=6m	A002ML1
	L=9m	A002ML2
	L=15m	A002ML3

OPAL screen (Direct Emission).
For LOGICO EASY System 57 - OPAL.

Accessories

Electrical Connector



	Driver	Colour	Code
	ON-OFF	●	A014MELB

L-shaped blind joint.
Sizes 818x818x80mm.
For LOGICO EASY System 57.

End Caps



	Colour	Code
	●	A003M2B

End caps (2 pieces).
For LOGICO EASY System 57 - OPAL / UGR19.

Canopy



	Colour	Code
	●	A004B

Canopy with 5 poles terminal block.
Feeding cable not included.

Cover Panel



	Colour	Code
	●	A005MB

Joint for screens.
To be used for configurations longer than 15 meters.
For LOGICO EASY System 57.

Bracket



	Code
	A007M

Bracket with adjustment system for suspended installation (2 pieces).
Two brackets needed for each lighting module.
For LOGICO EASY 57.

Suspension



	Version	Code
	L=6m	A008T
	L=5m	A008U
	L=4m	A008V
	L=3m	A008W
	L=2m	A008X
	L=1m	A008Y
	L=0,5m	A008Z

Suspension cable (2 pieces).

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

T010BV830ELDB | LOGICO EASY System 57 - OPAL / UGR19

LED luminaire for ceiling or suspended system installation. L module

Terminal Box



Version	Code
3 Poli ON-OFF	A009Z

Terminal block (plug/socket).

One for each power supply.

A009Z - For LOGICO EASY 37 | 57 | 100.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI