



T010MV840ELPW | LOGICO EASY System 57 - OPAL / UGR19 LED luminaire for ceiling or suspended system installation. L module



The fixture's photometric values
can be found on the following pages



SOURCE

LED Engine made of linear LED boards Ra80.

Energy efficiency class: D

Nominal power: 2x10W

Nominal flux: See photometries

Colour rendering index: 80

Rf: 84

Rg: 95

CCT nominal: 4000K

Lifetime (L80/B10): 100000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

Direct emission in two effect variants: diffused light - OPAL optics - and controlled light - UGR19 optics. Diffused light - OPAL optic: optical system made of a steel reflector with white polymer coating and a closing diffuser screen in opal anti-glare polycarbonate supplied in unrollable reels and available as a related code. Controlled light - UGR19 optic: optical system made of a steel reflector with white polymer coating and UGR closing diffuser screen supplied in unrollable reels and available as a related code (UGR<19 and L65<3000 cd/m² EN-12464-1).

Emission: DIRECT

Optic: REFLECTOR

Optical efficiency: 100%

Fixture flux: See photometries

Luminous efficacy: See photometries

Photobiological safety: Compliant with RG0 exempt risk group

MECHANICAL CHARACTERISTICS

Painted extruded aluminium body with 57mm section. Upper closing screen in white PVC.

Colour and finish: White

Dimensions: AxB=818x818mm

Weight: 3.42Kg

Version: L CONNECTOR

Degree of protection: IP40

Mechanical Resistance: IK02

ELECTRICAL CHARACTERISTICS

Integrated electronic ON-OFF driver. "Easy Connection" system for a quick connection between the modules of the system thanks to the pre-assembled plug/socket connection elements. Preset for through wiring allowing to reach a maximum length of 18 meters. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

Fixture Power: 2x12W

Power supply: 220-240Vac 50/60Hz

Insulation Class: CLASS 1

Type of driver / Control: ON-OFF

Driver included: YES

Class F: YES

SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

Ambient temperature: 0°C / +25°C

Relative humidity UR: <85%

INSTALLATION

To be completed with polycarbonate end caps, mounting systems for surface or suspended application and terminal block for connection to the power line.

NOTES

Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

REGULATIONS AND CERTIFICATIONS

CE.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

T010MV840ELPW | LOGICO EASY System 57 - OPAL / UGR19
LED luminaire for ceiling or suspended system installation. L module



	4000K	H(m)	D(m)	E _{max} (lx)		
	Ra80		111°			
Fixture Power	12W	1	2.90	371		
Source Flux	1050lm	2	5.80	93		
Fixture Flux	1050lm	3	8.70	41		
Efficacy	91lm/W	4	11.60	23		
G0300A	I _{max} =353cd/klm	I _{max}	371cd	5	14.49	15



	4000K	H(m)	D1(m)	D2(m)	E _{max} (lx)		
	Ra80		83°	89°			
Fixture Power	12W	1	1.78	1.97	572		
Source Flux	1036lm	2	3.56	3.94	143		
Fixture Flux	1036lm	3	5.33	5.91	64		
Efficacy	90lm/W	4	7.11	7.88	36		
G0300	I _{max} =552cd/klm	I _{max}	572cd	5	8.89	9.85	23

OP

Nominal flux 2x2099lm
 Fixture flux 2x1050lm
 Luminous efficacy 183lm/W

UGR

Nominal flux 2x2071lm
 Fixture flux 2x1036lm
 Luminous efficacy 180lm/W

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

Targetti Sankey S.r.l.
 Via Pratese, 164
 50145 Firenze - Italy
 Tel: +39 055 37911
 targetti.com
 targetti@targetti.com

CCIAA Firenze
 Share Capital:
 € 500.000,00
 VAT N. (IT):
 01537660480
 R.E.A.: FI-275656



We reserve the right to make technical changes.

T010MV840ELPW | LOGICO EASY System 57 - OPAL / UGR19
LED luminaire for ceiling or suspended system installation. L module

Related codes

Screen



Dimensions	Code
L=6m	A001ML1
L=9m	A001ML2
L=15m	A001ML3

UGR19 screen (Direct Emission).
 For LOGICO EASY System 57 - UGR19.



Dimensions	Code
L=6m	A002ML1
L=9m	A002ML2
L=15m	A002ML3

OPAL screen (Direct Emission).
 For LOGICO EASY System 57 - OPAL.

Accessories

Electrical Connector



Driver	Colour	Code
ON-OFF	<input type="radio"/>	A014MELW

L-shaped blind joint.
 Sizes 818x818x80mm.
 For LOGICO EASY System 57.

End Caps



Colour	Code
<input type="radio"/>	A003M2W

End caps (2 pieces).
 For LOGICO EASY System 57 - OPAL / UGR19.


Canopy



Colour	Code
<input type="radio"/>	A004W

Canopy with 5 poles terminal block.
 Feeding cable not included.

Cover Panel



Colour	Code
<input type="radio"/>	A005MW

Joint for screens.
 To be used for configurations longer than 15 meters.
 For LOGICO EASY System 57.

Bracket



Code
A006M

Bracket for ceiling installation (2 pieces).
 Two brackets needed for each lighting module.
 For LOGICO EASY 57.



Code
A007M

Bracket with adjustment system for suspended installation (2 pieces).
 Two brackets needed for each lighting module.
 For LOGICO EASY 57.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
 Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
 Via Pratese, 164
 50145 Firenze - Italy
 Tel: +39 055 37911
 targetti.com
 targetti@targetti.com

CCIAA Firenze
 Share Capital:
 € 500.000,00
 VAT N. (IT):
 01537660480
 R.E.A: FI-275656



T010MV840ELPW | LOGICO EASY System 57 - OPAL / UGR19
LED luminaire for ceiling or suspended system installation. L module

Suspension



	Version	Code
	L=6m	A008T
	L=5m	A008U
	L=4m	A008V
	L=3m	A008W
	L=2m	A008X
	L=1m	A008Y
	L=0,5m	A008Z

Suspension cable (2 pieces).

Terminal Box



	Version	Code
	3 Poli ON-OFF	A009Z

Terminal block (plug/socket).
 One for each power supply.
A009Z - For LOGICO EASY 37 | 57 | 100.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
 Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
 Via Pratese, 164
 50145 Firenze - Italy
 Tel: +39 055 37911
 targetti.com
 targetti@targetti.com

CCIAA Firenze
 Share Capital:
 € 500.000,00
 VAT N. (IT):
 01537660480
 R.E.A: FI-275656

