



**T011MW830ELPW | LOGICO EASY System 100 - OPAL HO**  
LED luminaire for ceiling or suspended system installation. Linear module



	3000K	H(m)	D(m)	E <sub>max</sub> (lx)		
	Ra80		109°			
	Fixture Power	99W	1	2.82	3234	
	Source Flux	8998lm	2	5.64	808	
	Fixture Flux	8998lm	3	8.46	359	
	Efficacy	91lm/W	4	11.28	202	
G0301A	I <sub>max</sub> =359cd/klm	I <sub>max</sub>	3235cd	5	14.10	129



**SOURCE**

LED Engine made of linear LED boards Ra80.  
**Energy efficiency class:** D  
**Nominal power:** 88W  
**Nominal flux:** 8998lm  
**Colour rendering index:** 80  
**Rf:** 84  
**Rg:** 95  
**CCT nominal:** 3000K  
**Lifetime (L80/B10):** 100000h tq +25°C

**ILLUMINOTECHNICAL CHARACTERISTICS**

Direct emission. Diffused light - OPAL High Output optic: optical system made of a steel reflector with white polymer coating and a closing diffuser screen in opal anti-glare polycarbonate supplied in unrollable reels and available as a related code.  
**Emission:** DIRECT  
**Optic:** REFLECTOR  
**Optical efficiency:** 100%  
**Fixture flux:** 8998lm  
**Luminous efficacy:** 91lm/W  
**Photobiological safety:** Compliant with RG0 exempt risk group

**MECHANICAL CHARACTERISTICS**

Painted extruded aluminium body with 100mm section. Upper closing screen in white PVC.  
**Colour and finish:** White  
**Dimensions:** L=2916mm  
**Weight:** 7.45Kg  
**Version:** LINEAR  
**Degree of protection:** IP40  
**Mechanical Resistance:** IK02

**ELECTRICAL CHARACTERISTICS**

Integrated electronic ON-OFF driver. "Easy Connection" system for a quick connection between the modules of the system thanks to the pre-assembled plug/socket connection elements. Preset for through wiring allowing to reach a maximum length of 18 meters. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.  
**Fixture Power:** 99W  
**Power supply:** 220-240Vac 50/60Hz  
**Insulation Class:** CLASS 1  
**Type of driver / Control:** ON-OFF  
**Driver included:** YES  
**Class F:** YES  
**SAFE FLICKER:** PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light  
**Ambient temperature:** 0°C / +25°C  
**Relative humidity UR:** <85%

**INSTALLATION**

To be completed with polycarbonate end caps, mounting systems for surface or suspended application and terminal block for connection to the power line.

**NOTES**

For angular configurations L light modules and the L blind joint accessory are available. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

**REGULATIONS AND CERTIFICATIONS**

CE.

**WARRANTY**

5 years.

**WARNING**

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
 Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

Targetti Sankey S.r.l.  
 Via Pratese, 164  
 50145 Firenze - Italy  
 Tel: +39 055 37911  
 targetti.com  
 targetti@targetti.com

CCIAA Firenze  
 Share Capital:  
 € 500.000,00  
 VAT N. (IT):  
 01537660480  
 R.E.A: FI-275656



We reserve the right to make technical changes.

**T011MW830ELPW | LOGICO EASY System 100 - OPAL HO**  
**LED luminaire for ceiling or suspended system installation. Linear module**

**Related codes**

**Screen**



Dimensions	Code
L=6m	<b>A002LL1</b>
L=9m	<b>A002LL2</b>
L=15m	<b>A002LL3</b>

OPAL screen (Direct Emission).  
 For LOGICO EASY System 100 - OPAL.

**Accessories**

**End Caps**



Colour	Code
○	<b>A003L1W</b>

End caps (2 pieces).  
 For LOGICO EASY System 100.

**Canopy**



Colour	Code
○	<b>A004W</b>

Canopy with 5 poles terminal block.  
 Feeding cable not included.

**Cover Panel**



Colour	Code
○	<b>A005LW</b>

Joint for screens.  
 To be used for configurations longer than 15 meters.  
 For LOGICO EASY System 100.

**Bracket**



Code
<b>A006L</b>

Bracket for ceiling installation (2 pieces).  
 Two brackets needed for each lighting module.  
 For LOGICO EASY 100.



Code
<b>A007L</b>

Bracket with adjustment system for suspended installation (2 pieces).  
 Two brackets needed for each lighting module.  
 For LOGICO EASY 100.

*Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.*  
*Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).*

We reserve the right to make technical changes.

Targetti Sankey S.r.l.  
 Via Pratese, 164  
 50145 Firenze - Italy  
 Tel: +39 055 37911  
 targetti.com  
 targetti@targetti.com

CCIAA Firenze  
 Share Capital:  
 € 500.000,00  
 VAT N. (IT):  
 01537660480  
 R.E.A: FI-275656



**T011MW830ELPW | LOGICO EASY System 100 - OPAL HO**  
**LED luminaire for ceiling or suspended system installation. Linear module**

**Suspension**



	Version	Code
	L=6m	<b>A008T</b>
	L=5m	<b>A008U</b>
	L=4m	<b>A008V</b>
	L=3m	<b>A008W</b>
	L=2m	<b>A008X</b>
	L=1m	<b>A008Y</b>
	L=0,5m	<b>A008Z</b>

Suspension cable (2 pieces).

**Terminal Box**



	Version	Code
	3 Poli ON-OFF	<b>A009Z</b>

Terminal block (plug/socket).  
 One for each power supply.  
**A009Z** - For LOGICO EASY 37 | 57 | 100.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
 Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.  
 Via Pratese, 164  
 50145 Firenze - Italy  
 Tel: +39 055 37911  
 targetti.com  
 targetti@targetti.com

CCIAA Firenze  
 Share Capital:  
 € 500.000,00  
 VAT N. (IT):  
 01537660480  
 R.E.A: FI-275656

