


## T016MV940ELDB | LOGICO EASY System 100 - OPAL / UGR19 LED luminaire for ceiling or suspended system installation. L module



The fixture's photometric values  
can be found on the following pages



### SOURCE

LED Engine made of linear LED boards Ra90.

**Energy efficiency class:** E

**Nominal power:** 2x17,5W

**Nominal flux:** See photometries

**Colour rendering index:** 90

**Rf:** 92

**Rg:** 101

**CCT nominal:** 4000K

**Lifetime (L80/B10):** 100000h tq +25°C

### ILLUMINOTECHNICAL CHARACTERISTICS

Direct emission in two effect variants: diffused light - OPAL optics - and controlled light - UGR19 optics. Diffused light - OPAL optic: optical system made of a steel reflector with white polymer coating and a closing diffuser screen in opal anti-glare polycarbonate supplied in unrollable reels and available as a related code. Controlled light - UGR19 optic: optical system made of a steel reflector with white polymer coating and UGR closing diffuser screen supplied in unrollable reels and available as a related code (UGR<19 and L65<3000 cd/m<sup>2</sup> EN-12464-1).

**Emission:** DIRECT

**Optic:** REFLECTOR

**Optical efficiency:** 100%

**Fixture flux:** See photometries

**Luminous efficacy:** See photometries

**Photobiological safety:** Compliant with RG0 exempt risk group

### MECHANICAL CHARACTERISTICS

Painted extruded aluminium body with 100mm section. Upper closing screen in black PVC.

**Colour and finish:** Black

**Dimensions:** AxB=812x812mm

**Weight:** 3.7Kg

**Version:** L CONNECTOR

**Degree of protection:** IP40

**Mechanical Resistance:** IK02

### ELECTRICAL CHARACTERISTICS

Integrated electronic ON-OFF driver. "Easy Connection" system for a quick connection between the modules of the system thanks to the pre-assembled plug/socket connection elements. Preset for through wiring allowing to reach a maximum length of 18 meters. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

**Fixture Power:** 2x20W

**Power supply:** 220-240Vac 50/60Hz

**Insulation Class:** CLASS 1

**Type of driver / Control:** ON-OFF

**Driver included:** YES

**Class F:** YES

**SAFE FLICKER:** PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

**Ambient temperature:** 0°C / +25°C

**Relative humidity UR:** <85%

### INSTALLATION

To be completed with polycarbonate end caps, mounting systems for surface or suspended application and terminal block for connection to the power line.

### NOTES

Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

### REGULATIONS AND CERTIFICATIONS

CE.

### WARRANTY

5 years.

### WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.  
Via Pratese, 164  
50145 Firenze - Italy  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

CCIAA Firenze  
Share Capital:  
€ 500.000,00  
VAT N. (IT):  
01537660480  
R.E.A: FI-275656

**TARGETTI**

**T016MV940ELDB | LOGICO EASY System 100 - OPAL / UGR19**  
**LED luminaire for ceiling or suspended system installation. L module**



|               | 4000K                       | H(m)             | D(m)  | Emax(lx) |       |    |
|---------------|-----------------------------|------------------|-------|----------|-------|----|
|               | Ra90                        |                  |       | 109°     |       |    |
| Fixture Power | 20W                         | 1                | 2.82  | 572      |       |    |
| Source Flux   | 1591lm                      | 2                | 5.64  | 143      |       |    |
| Fixture Flux  | 1591lm                      | 3                | 8.46  | 64       |       |    |
| Efficacy      | 80lm/W                      | 4                | 11.28 | 36       |       |    |
| G0301A        | I <sub>max</sub> =359cd/klm | I <sub>max</sub> | 572cd | 5        | 14.10 | 23 |



|               | 4000K                       | H(m)             | D(m)  | Emax(lx) |      |    |
|---------------|-----------------------------|------------------|-------|----------|------|----|
|               | Ra90                        |                  |       | 88°      |      |    |
| Fixture Power | 20W                         | 1                | 1.94  | 808      |      |    |
| Source Flux   | 1541lm                      | 2                | 3.88  | 202      |      |    |
| Fixture Flux  | 1541lm                      | 3                | 5.83  | 90       |      |    |
| Efficacy      | 77lm/W                      | 4                | 7.77  | 51       |      |    |
| G0301         | I <sub>max</sub> =525cd/klm | I <sub>max</sub> | 808cd | 5        | 9.71 | 32 |

**OP**

Nominal flux 2x3181lm  
 Fixture flux 2x1591lm  
 Luminous efficacy 159lm/W

**UGR**

Nominal flux 2x3081lm  
 Fixture flux 2x1541lm  
 Luminous efficacy 154lm/W

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process. Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

Targetti Sankey S.r.l.  
 Via Pratese, 164  
 50145 Firenze - Italy  
 Tel: +39 055 37911  
 targetti.com  
 targetti@targetti.com

CCIAA Firenze  
 Share Capital:  
 € 500.000,00  
 VAT N. (IT):  
 01537660480  
 R.E.A: FI-275656



We reserve the right to make technical changes.

## T016MV940ELDB | LOGICO EASY System 100 - OPAL / UGR19 LED luminaire for ceiling or suspended system installation. L module

### Related codes

#### Screen



| Dimensions | Code           |
|------------|----------------|
| L=6m       | <b>A001LL1</b> |
| L=9m       | <b>A001LL2</b> |
| L=15m      | <b>A001LL3</b> |

UGR19 screen (Direct Emission).  
For LOGICO EASY System 100 - UGR19.



| Dimensions | Code           |
|------------|----------------|
| L=6m       | <b>A002LL1</b> |
| L=9m       | <b>A002LL2</b> |
| L=15m      | <b>A002LL3</b> |

OPAL screen (Direct Emission).  
For LOGICO EASY System 100 - OPAL.

### Accessories

#### End Caps



| Colour | Code           |
|--------|----------------|
|        | <b>A003L1B</b> |

End caps (2 pieces).  
For LOGICO EASY System 100.

#### Canopy



| Colour | Code         |
|--------|--------------|
|        | <b>A004B</b> |

Canopy with 5 poles terminal block.  
Feeding cable not included.

#### Cover Panel



| Colour | Code          |
|--------|---------------|
|        | <b>A005LB</b> |

Joint for screens.  
To be used for configurations longer than 15 meters.  
For LOGICO EASY System 100.

#### Bracket



| Code         |
|--------------|
| <b>A006L</b> |

Bracket for ceiling installation (2 pieces).  
Two brackets needed for each lighting module.  
For LOGICO EASY 100.



| Code         |
|--------------|
| <b>A007L</b> |

Bracket with adjustment system for suspended installation (2 pieces).  
Two brackets needed for each lighting module.  
For LOGICO EASY 100.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.  
Via Pratese, 164  
50145 Firenze - Italy  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

CCIAA Firenze  
Share Capital:  
€ 500.000,00  
VAT N. (IT):  
01537660480  
R.E.A: FI-275656

**TARGETTI**

**T016MV940ELDB | LOGICO EASY System 100 - OPAL / UGR19**  
**LED luminaire for ceiling or suspended system installation. L module**

**Suspension**



|  | Version | Code         |
|--|---------|--------------|
|  | L=6m    | <b>A008T</b> |
|  | L=5m    | <b>A008U</b> |
|  | L=4m    | <b>A008V</b> |
|  | L=3m    | <b>A008W</b> |
|  | L=2m    | <b>A008X</b> |
|  | L=1m    | <b>A008Y</b> |
|  | L=0,5m  | <b>A008Z</b> |

Suspension cable (2 pieces).

**Terminal Box**



|  | Version       | Code         |
|--|---------------|--------------|
|  | 3 Poli ON-OFF | <b>A009Z</b> |

Terminal block (plug/socket).  
 One for each power supply.  
**A009Z** - For LOGICO EASY 37 | 57 | 100.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
 Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.  
 Via Pratese, 164  
 50145 Firenze - Italy  
 Tel: +39 055 37911  
 targetti.com  
 targetti@targetti.com

CCIAA Firenze  
 Share Capital:  
 € 500.000,00  
 VAT N. (IT):  
 01537660480  
 R.E.A: FI-275656

