T017MX840ELPW | LOGICO EASY Stand Alone 37 - OPAL
Linear stand alone LED fixture for ceiling mounted or suspension installation





4000K		H(m)	D(m)	Emax(lx)
Ra80			113°	
Fixture Power	47W	1	3.00	1433
Source Flux	4128lm	2	6.00	358
Fixture Flux	4128lm	3	9.00	159
Efficacy	88lm/W	4	12.00	90
6000843a Imax=347cd/klm	Imax	1434cd	5	15.00	57



The figures on the drawing are expressed in mm.

SOURCE

LED Engine made of linear LED boards Ra80.
Energy efficiency class: D
Nominal power: 40W
Nominal flux: 4128lm
Colour rendering index: 80
Rf: 84
Rg: 95
CCT nominal: 4000K
Lifetime (L80/B10): 100000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

Direct emission. Diffused light - OPAL optic: optical system made of a steel reflector with white polymer coating and a closing diffuser screen in opal anti-glare polycarbonate.
Emission: DIRECT
Optic: REFLECTOR
Optical efficiency: 100%
Fixture flux: 4128lm
Luminous efficacy: 88lm/W
Photobiological safety: Compliant with RG0 exempt risk group

MECHANICAL CHARACTERISTICS

Painted extruded aluminium body with 37mm section and polycarbonate end caps. Upper closing screen in white PVC.
Colour and finish: White
Dimensions: L=2340mm
Weight: 5.09Kg
Version: LINEAR
Degree of protection: IP40
Mechanical Resistance: IK02

ELECTRICAL CHARACTERISTICS

Integrated electronic ON-OFF driver. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.
Fixture Power: 47W
Power supply: 220-240Vac 50/60Hz
Insulation Class: CLASS 1
Type of driver / Control: ON-OFF
Driver included: YES
Class F: YES
SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light
Ambient temperature: 0°C / +25°C
Relative humidity UR: <85%

INSTALLATION

To be completed with mounting systems for surface or suspended application.

REGULATIONS AND CERTIFICATIONS

CE.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

T017MX840ELPW | LOGICO EASY Stand Alone 37 - OPAL
Linear stand alone LED fixture for ceiling mounted or suspension installation

Accessories

Canopy

	Colour	Code
	◯	**A004W**

Canopy with 5 poles terminal block.
Feeding cable not included.

Bracket

	Code
	A006S

Bracket for ceiling installation (2 pieces).
Two brackets needed for each lighting module.
For LOGICO EASY 37.

	Code
	A007S

Bracket with adjustment system for suspended installation (2 pieces).
Two brackets needed for each lighting module.
For LOGICO EASY 37.

Suspension

	Version	Code
	L=6m	**A008T**
	L=5m	**A008U**
	L=4m	**A008V**
	L=3m	**A008W**
	L=2m	**A008X**
	L=1m	**A008Y**
	L=0,5m	**A008Z**

Suspension cable (2 pieces).

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI