



T019MY840ELDB | LOGICO EASY Stand Alone 57 - OPAL HO

Linear stand alone LED fixture for ceiling mounted or suspension installation



	4000K	H(m)	D(m)	E _{max} (lx)
	Ra80		111°	
Fixture Power	33W	1	2.90	1008
Source Flux	2852lm	2	5.80	252
Fixture Flux	2852lm	3	8.70	112
Efficacy	86lm/W	4	11.60	63
G0300A	I _{max} =353cd/klm	I _{max}	1008cd	5
			14.49	40



SOURCE

LED Engine made of linear LED boards Ra80.

Energy efficiency class: D

Nominal power: 30W

Nominal flux: 2852lm

Colour rendering index: 80

Rf: 84

Rg: 95

CCT nominal: 4000K

Lifetime (L80/B10): 100000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

Direct emission. Diffused light - OPAL High Output optic: optical system made of a steel reflector with white polymer coating and a closing diffuser screen in opal anti-glare polycarbonate.

Emission: DIRECT

Optic: REFLECTOR

Optical efficiency: 100%

Fixture flux: 2852lm

Luminous efficacy: 86lm/W

Photobiological safety: Compliant with RG0 exempt risk group

MECHANICAL CHARACTERISTICS

Painted extruded aluminium body with 57mm section and polycarbonate end caps. Upper closing screen in black PVC.

Colour and finish: Black

Dimensions: L=1462mm

Weight: 3.05Kg

Version: LINEAR

Degree of protection: IP40

Mechanical Resistance: IK02

ELECTRICAL CHARACTERISTICS

Integrated electronic ON-OFF driver. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC.

Fixture Power: 33W

Power supply: 220-240Vac 50/60Hz

Insulation Class: CLASS 1

Type of driver / Control: ON-OFF

Driver included: YES

Class F: YES

SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

Ambient temperature: 0°C / +25°C

Relative humidity UR: <85%

INSTALLATION

To be completed with mounting systems for surface or suspended application.

NOTES

Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

REGULATIONS AND CERTIFICATIONS

CE.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

T019MY840ELDB | LOGICO EASY Stand Alone 57 - OPAL HO

Linear stand alone LED fixture for ceiling mounted or suspension installation

Accessories

Canopy



Colour	Code
	A004B



Canopy with 5 poles terminal block.
Feeding cable not included.

Bracket



Code
A006M

Bracket for ceiling installation (2 pieces).
Two brackets needed for each lighting module.
For LOGICO EASY 57.



Code
A007M

Bracket with adjustment system for suspended installation (2 pieces).
Two brackets needed for each lighting module.
For LOGICO EASY 57.

Suspension



Version	Code
L=6m	A008T
L=5m	A008U
L=4m	A008V
L=3m	A008W
L=2m	A008X
L=1m	A008Y
L=0,5m	A008Z

Suspension cable (2 pieces).

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI