



T026MY830ELPW | LOGICO EASY Stand Alone 100 - UGR19**Linear stand alone LED fixture for ceiling mounted or suspension installation. Emergency version**

	3000K	H(m)	D(m)	Emax(lx)		
	Ra80		88°			
	Fixture Power	40W	1	1.94	1986	
	Source Flux	3788lm	2	3.88	497	
	Fixture Flux	3788lm	3	5.83	221	
	Efficacy	95lm/W	4	7.77	124	
G0301	Imax=525cd/klm	Imax	1987cd	5	9.71	79



The figures on the drawing are expressed in mm.

SOURCE

LED Engine made of linear LED boards Ra80.

Energy efficiency class: D**Nominal power:** 34W**Nominal flux:** 3788lm**Colour rendering index:** 80**Rf:** 84**Rg:** 95**CCT nominal:** 3000K**Lifetime (L80/B10):** 100000h tq +25°C**ILLUMINOTECHNICAL CHARACTERISTICS**

Direct emission. Controlled light - UGR19 optics: optical system made of a steel reflector with white polymer coating and UGR closing diffuser screen (UGR<19 and L65<3000 cd/m² EN-12464-1).

Emission: DIRECT**Optic:** REFLECTOR**Optical efficiency:** 100%**Fixture flux:** 3788lm**Emergency fixture flux BLF:** 11%**Luminous efficacy:** 95lm/W**Photobiological safety:** Compliant with RG0 exempt risk group**MECHANICAL CHARACTERISTICS**

Painted extruded aluminium body with 100mm section and polycarbonate end caps. Upper closing screen in white PVC.

Colour and finish: White**Dimensions:** L=1462mm**Weight:** 5.45Kg**Version:** LINEAR**Degree of protection:** IP40**Mechanical Resistance:** IK02**ELECTRICAL CHARACTERISTICS**

Integrated electronic ON-OFF driver. Equipped with emergency pack - permanent emergency (1h autonomy and 24h recharge).

Fixture Power: 40W**Power supply:** 220-240Vac 50/60Hz**Insulation Class:** CLASS 1**Type of driver / Control:** ON-OFF (EMERGENCY VERSION)**Driver included:** YES**Class F:** YES**SAFE FLICKER:** PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light**Ambient temperature:** 0°C / +25°C**Relative humidity UR:** <85%**INSTALLATION**

To be completed with mounting systems for surface or suspended application.

NOTES

Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

REGULATIONS AND CERTIFICATIONS

CE.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

T026MY830ELPW | LOGICO EASY Stand Alone 100 - UGR19

Linear stand alone LED fixture for ceiling mounted or suspension installation. Emergency version

Accessories

Canopy



Colour Code

○ **A004W**

Canopy with 5 poles terminal block.
Feeding cable not included.

Bracket



Code

A006L

Bracket for ceiling installation (2 pieces).
Two brackets needed for each lighting module.
For LOGICO EASY 100.



Code

A007L

Bracket with adjustment system for suspended installation (2 pieces).
Two brackets needed for each lighting module.
For LOGICO EASY 100.

Suspension



Version Code

L=6m **A008T**

L=5m **A008U**

L=4m **A008V**

L=3m **A008W**

L=2m **A008X**

L=1m **A008Y**

L=0,5m **A008Z**

Suspension cable (2 pieces).

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI