


T028MX930ELDB | LOGICO EASY System 57 - UGR16

Linear LED fixture for ceiling mounted or suspension system installation. Emergency version



	3000K	H(m)	D1(m)	D2(m)	Emax(lx)	
	Ra90	76°	58°			
Fixture Power	28W	1	1.55	1.10	2141	
Source Flux	2444lm	2	3.10	2.20	535	
Fixture Flux	2444lm	3	4.65	3.30	238	
Efficacy	87lm/W	4	6.20	4.40	134	
6000760 I _{max} =1024cd/klm	I _{max}	2503cd	5	7.75	5.49	86



SOURCE

LED Engine made of linear LED boards Ra90.

Energy efficiency class: D

Nominal power: 24W

Nominal flux: 2444lm

Colour rendering index: 90

Rf: 92

Rg: 101

CCT nominal: 3000K

Lifetime (L80/B10): 100000h tq +25°C

ILLUMINOTECHNICAL CHARACTERISTICS

Direct emission. Controlled light. UGR16 Optics: optical system made of lenses with differentiated facets for optimizing the direction of the luminous flux and cellular optics in black anti-glare polycarbonate (UGR<16 and L65<200 cd/m² EN-12464-1).

Emission: DIRECT

Optic: CELLULAR

Optical efficiency: 100%

Fixture flux: 2444lm

Emergency fixture flux BLF: 21.5%

Luminous efficacy: 87lm/W

Photobiological safety: Compliant with RG0 exempt risk group

MECHANICAL CHARACTERISTICS

Painted extruded aluminium body with 57mm section. Upper closing screen in black PVC.

Colour and finish: Black

Dimensions: L=2348mm

Weight: 7.07Kg

Version: LINEAR

Degree of protection: IP40

Mechanical Resistance: IK02

ELECTRICAL CHARACTERISTICS

Integrated electronic ON-OFF driver. "Easy Connection" system for a quick connection between the modules of the system thanks to the pre-assembled plug/socket connection elements. Preset for through wiring allowing to reach a maximum length of 18 meters. Equipped with emergency pack - permanent emergency (1h autonomy and 24h recharge).

Fixture Power: 28W

Power supply: 220-240Vac 50/60Hz

Insulation Class: CLASS 1

Type of driver / Control: ON-OFF (EMERGENCY VERSION)

Driver included: YES

Class F: YES

SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

Ambient temperature: 0°C / +25°C

Relative humidity UR: <85%

INSTALLATION

To be completed with polycarbonate end caps, mounting systems for surface or suspended application and terminal block for connection to the power line.

NOTES

For angular configurations the L blind joint accessory is available. Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

REGULATIONS AND CERTIFICATIONS

CE.

WARRANTY

5 years.

WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
Via Pratese, 164
50145 Firenze - Italy
Tel: +39 055 37911
targetti.com
targetti@targetti.com

CCIAA Firenze
Share Capital:
€ 500.000,00
VAT N. (IT):
01537660480
R.E.A: FI-275656

TARGETTI

T028MX930ELDB | LOGICO EASY System 57 - UGR16
 Linear LED fixture for ceiling mounted or suspension system installation. Emergency version

Accessories

Electrical Connector



Driver	Colour	Code
ON-OFF	●	A014MELB

L-shaped blind joint.
 Sizes 818x818x80mm.
 For LOGICO EASY System 57.

End Caps



Colour	Code
●	A003M1B

End caps (2 pieces).
 For LOGICO EASY System 57 - UGR16.

Canopy



Colour	Code
●	A004B

Canopy with 5 poles terminal block.
 Feeding cable not included.

Bracket



Code
A006M

Bracket for ceiling installation (2 pieces).
 Two brackets needed for each lighting module.
 For LOGICO EASY 57.



Code
A007M

Bracket with adjustment system for suspended installation (2 pieces).
 Two brackets needed for each lighting module.
 For LOGICO EASY 57.

Suspension



Version	Code
L=6m	A008T
L=5m	A008U
L=4m	A008V
L=3m	A008W
L=2m	A008X
L=1m	A008Y
L=0,5m	A008Z

Suspension cable (2 pieces).

Terminal Box



Version	Code
3 Poli ON-OFF	A009Z

Terminal block (plug/socket).
 One for each power supply.
A009Z - For LOGICO EASY 37 | 57 | 100.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.
 Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.
 Via Pratese, 164
 50145 Firenze - Italy
 Tel: +39 055 37911
 targetti.com
 targetti@targetti.com

CCIAA Firenze
 Share Capital:
 € 500.000,00
 VAT N. (IT):
 01537660480
 R.E.A: FI-275656

