



## T030BX940ELDB | LOGICO EASY Stand Alone 57 - UGR16

Linear stand alone LED fixture for ceiling mounted or suspension installation. Emergency version



		4000K	H(m)	D1(m)	D2(m)	E <sub>max</sub> (lx)
		Ra90	76°	58°		
Fixture Power	72W	1	1.55	1.10	2240	
Source Flux	6898lm	2	3.10	2.20	560	
Fixture Flux	6899lm	3	4.65	3.30	249	
Efficacy	96lm/W	4	6.20	4.40	140	
6000760	I <sub>max</sub> =380cd/klm	I <sub>max</sub>	2619cd	5	7.75	5.49 90



### SOURCE

LED Engine made of linear LED boards Ra90.

**Energy efficiency class:** D, E

**Nominal power:** 62W

**Nominal flux:** 6898lm

**Colour rendering index:** 90

**Rf:** 92

**Rg:** 101

**CCT nominal:** 4000K

**Lifetime (L80/B10):** 100000h tq +25°C

### ILLUMINOTECHNICAL CHARACTERISTICS

Direct/indirect emission. Controlled light. UGR16 Optics: optical system made of lenses with differentiated facets for optimizing the direction of the luminous flux and cellular optics in black anti-glare polycarbonate (UGR<16 and L65<200 cd/m<sup>2</sup> EN-12464-1).

**Emission:** DIRECT/INDIRECT

**Optic:** CELLULAR

**Optical efficiency:** 100%

**Fixture flux:** 6898lm

**Emergency fixture flux BLF:** 21.5% (Direct emission)

**Luminous efficacy:** 96lm/W

**Photobiological safety:** Compliant with RG0 exempt risk group

### MECHANICAL CHARACTERISTICS

Painted extruded aluminium body with 57mm section and polycarbonate end caps. Upper closing screen in translucent polycarbonate.

**Colour and finish:** Black

**Dimensions:** L=2352mm

**Weight:** 7.16Kg

**Version:** LINEAR

**Degree of protection:** IP40

**Mechanical Resistance:** IK02

### ELECTRICAL CHARACTERISTICS

Integrated electronic ON-OFF driver. Equipped with emergency pack - permanent emergency (1h autonomy and 24h recharge).

**Fixture Power:** 72W

**Power supply:** 220-240Vac 50/60Hz

**Insulation Class:** CLASS 1

**Type of driver / Control:** ON-OFF (EMERGENCY VERSION)

**Driver included:** YES

**Class F:** YES

**SAFE FLICKER:** PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light

**Ambient temperature:** 0°C / +25°C

**Relative humidity UR:** <85%

### INSTALLATION

To be completed with mounting systems for surface or suspended application.

### NOTES

Commissioning of the control system via free APP; the intervention of a specialist technician can be quoted on request.

### REGULATIONS AND CERTIFICATIONS

CE.

### WARRANTY

5 years.

### WARNING

Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.

Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.  
Via Pratese, 164  
50145 Firenze - Italy  
Tel: +39 055 37911  
targetti.com  
targetti@targetti.com

CCIAA Firenze  
Share Capital:  
€ 500.000,00  
VAT N. (IT):  
01537660480  
R.E.A.: FI-275656

**TARGETTI**

**T030BX940ELDB | LOGICO EASY Stand Alone 57 - UGR16**  
 Linear stand alone LED fixture for ceiling mounted or suspension installation. Emergency version

**Accessories**

**Canopy**



Colour	Code
●	<b>A004B</b>

Canopy with 5 poles terminal block.  
 Feeding cable not included.

**Bracket**



Code

**A007M**

Bracket with adjustment system for suspended installation (2 pieces).  
 Two brackets needed for each lighting module.  
 For LOGICO EASY 57.

**Suspension**



Version	Code
L=6m	<b>A008T</b>
L=5m	<b>A008U</b>
L=4m	<b>A008V</b>
L=3m	<b>A008W</b>
L=2m	<b>A008X</b>
L=1m	<b>A008Y</b>
L=0,5m	<b>A008Z</b>

Suspension cable (2 pieces).

Due to the technological evolution of the electronic components, the data provided may be updated, and as such, confirmation must be requested during the order process.  
 Luminous flux and power supply have +/-10% tolerances with respect to the indicated value. tq +25°C (CIE 121).

We reserve the right to make technical changes.

Targetti Sankey S.r.l.  
 Via Pratese, 164  
 50145 Firenze - Italy  
 Tel: +39 055 37911  
 targetti.com  
 targetti@targetti.com

CCIAA Firenze  
 Share Capital:  
 € 500.000,00  
 VAT N. (IT):  
 01537660480  
 R.E.A: FI-275656

